

Monthly WIM Distribution for 08/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	156	15,152	6,609	125	696	297	32	58	491	84	4	6	57	218	0
	Flex	0.00	0.00	0.00	1.46	0.43	1.36	1.79	0.59	1.69	1.59	1.18	0.84	1.60	1.23	0.00
	Rigid	0.00	0.00	0.00	1.86	0.46	2.35	3.78	0.70	2.78	3.09	1.16	0.94	2.88	1.42	0.00
	GVW	3.9	3.1	5.5	31.2	18.6	37.7	63.1	32.0	59.4	68.6	57.8	56.2	78.0	21.6	0.0
SW DIR	Num	65	7,630	3,390	62	330	121	5	30	268	48	2	3	34	99	0
	Flex	0.00	0.00	0.00	1.27	0.32	1.05	1.69	0.45	1.84	1.57	1.36	0.87	1.60	0.95	0.00
	Rigid	0.00	0.00	0.00	1.57	0.34	1.77	3.67	0.55	3.05	3.06	1.35	1.03	2.76	1.08	0.00
	GVW	3.6	3.2	5.7	29.9	17.9	35.1	59.4	29.8	61.0	64.9	65.1	54.9	71.6	20.7	0.0
NE DIR	Num	91	7,522	3,219	63	365	176	26	28	223	36	2	3	22	119	0
	Flex	0.00	0.00	0.00	1.64	0.53	1.58	1.91	0.73	1.50	1.93	1.22	1.01	1.84	1.47	0.00
	Rigid	0.00	0.00	0.00	2.14	0.58	2.74	4.03	0.86	2.46	3.74	1.20	1.07	3.66	1.72	0.00
	GVW	4.1	3.1	5.4	32.4	19.2	39.3	64.6	34.2	57.4	85.9	60.8	71.6	86.9	22.5	0.0
SW 1	Num	56	5,429	2,442	53	295	107	5	26	236	42	1	2	31	86	0
	Flex	0.00	0.00	0.00	1.35	0.32	1.13	1.85	0.49	1.94	1.61	1.58	0.92	1.56	0.92	0.00
	Rigid	0.00	0.00	0.00	1.67	0.34	1.92	3.96	0.60	3.21	3.17	1.58	1.09	2.70	1.04	0.00
	GVW	3.6	3.2	6.1	30.3	18.0	36.1	59.9	30.7	62.2	66.0	72.3	53.7	71.2	21.0	0.0
SW 2	Num	10	2,202	947	9	35	14	1	4	33	7	0	1	4	14	0
	Flex	0.00	0.00	0.00	0.84	0.26	0.39	2.48	0.27	1.16	1.51	1.86	0.43	2.50	1.13	0.00
	Rigid	0.00	0.00	0.00	1.02	0.28	0.56	5.60	0.28	1.83	2.97	1.78	0.46	4.55	1.31	0.00
	GVW	3.6	3.0	4.5	28.0	17.1	27.1	88.0	28.7	51.4	64.4	173.7	70.0	87.3	18.1	0.0
NE 2	Num	11	2,112	832	7	30	12	2	3	28	5	0	0	2	10	0
	Flex	0.00	0.00	0.00	0.94	0.39	0.53	1.29	0.48	0.89	1.02	2.98	0.00	1.99	1.74	0.00
	Rigid	0.00	0.00	0.00	1.09	0.43	0.80	2.68	0.50	1.37	2.00	2.89	0.00	4.12	2.08	0.00
	GVW	3.7	3.0	4.5	26.3	17.7	32.8	71.0	36.8	50.5	64.7	169.7	0.0	98.8	20.2	0.0
NE 1	Num	80	5,410	2,387	56	335	165	24	26	194	31	2	3	20	109	0
	Flex	0.00	0.00	0.00	1.74	0.54	1.66	2.03	0.76	1.59	2.07	1.35	1.01	1.90	1.45	0.00
	Rigid	0.00	0.00	0.00	2.27	0.59	2.88	4.29	0.90	2.62	4.02	1.32	1.07	3.79	1.69	0.00
	GVW	4.1	3.2	5.7	33.2	19.3	40.2	65.9	34.4	58.4	88.8	66.1	71.6	87.7	22.6	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9