

Monthly WIM Distribution for 09/2011

Site Names: 00096, Rigby WIM
 County: Jefferson (26)
 Funct. Class: R Principal Arterial - Other
 Location: US-20 1.4 Mi. S of US-20B

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	95	15,296	6,368	120	550	195	18	59	643	125	3	5	74	166	0
	Flex	0.00	0.00	0.00	1.24	0.39	1.07	1.36	0.52	1.58	1.46	0.99	0.68	2.03	0.95	0.00
	Rigid	0.00	0.00	0.00	1.50	0.41	1.82	2.96	0.62	2.60	2.87	0.97	0.75	3.47	1.13	0.00
	GVW	3.9	3.1	5.2	29.1	18.6	34.8	58.0	31.7	57.5	63.3	53.7	56.2	80.7	22.5	0.0
SW DIR	Num	35	7,691	3,224	58	281	61	2	31	340	73	2	3	47	62	0
	Flex	0.00	0.00	0.00	1.28	0.33	0.89	3.68	0.41	1.77	1.18	0.67	0.49	2.28	0.87	0.00
	Rigid	0.00	0.00	0.00	1.51	0.35	1.48	8.73	0.50	2.92	2.27	0.66	0.56	3.69	1.09	0.00
	GVW	3.6	3.1	5.4	28.3	18.3	31.9	81.9	29.6	59.7	55.3	47.6	51.8	79.9	22.9	0.0
NE DIR	Num	61	7,605	3,144	62	269	134	16	28	303	53	2	3	27	104	0
	Flex	0.00	0.00	0.00	1.19	0.44	1.15	1.31	0.63	1.36	1.85	1.26	0.91	1.59	1.00	0.00
	Rigid	0.00	0.00	0.00	1.49	0.48	1.97	2.85	0.75	2.23	3.69	1.23	1.00	3.13	1.16	0.00
	GVW	4.1	3.0	5.1	29.8	19.0	36.1	57.4	33.7	54.9	74.1	55.8	66.0	82.2	22.3	0.0
SW 1	Num	29	5,408	2,353	48	244	54	2	28	303	62	2	2	42	53	0
	Flex	0.00	0.00	0.00	1.27	0.33	0.93	3.93	0.42	1.81	1.13	0.68	0.44	2.21	0.93	0.00
	Rigid	0.00	0.00	0.00	1.49	0.35	1.56	9.33	0.51	2.99	2.21	0.67	0.50	3.53	1.17	0.00
	GVW	3.5	3.1	5.6	28.0	18.4	32.4	86.7	29.8	60.2	54.8	47.2	51.4	78.5	24.0	0.0
SW 2	Num	5	2,283	871	10	36	7	0	4	37	10	0	0	6	9	0
	Flex	0.00	0.00	0.00	1.35	0.35	0.63	0.00	0.39	1.43	1.54	0.00	3.31	2.89	0.56	0.00
	Rigid	0.00	0.00	0.00	1.60	0.38	0.94	0.00	0.48	2.29	2.90	0.00	3.48	5.21	0.68	0.00
	GVW	3.6	3.0	4.7	29.5	17.5	31.4	0.0	27.9	55.3	59.3	0.0	209.6	89.5	16.3	0.0
NE 2	Num	7	2,136	800	7	28	7	1	3	35	9	0	0	4	11	0
	Flex	0.00	0.00	0.00	1.18	0.26	0.67	1.70	0.54	0.88	1.37	3.91	2.32	1.92	0.48	0.00
	Rigid	0.00	0.00	0.00	1.42	0.27	1.09	3.22	0.68	1.38	2.71	3.70	2.46	4.07	0.55	0.00
	GVW	3.8	3.0	4.6	30.2	17.5	29.4	55.2	33.2	46.5	64.7	290.5	193.5	69.0	14.6	0.0
NE 1	Num	53	5,470	2,344	55	241	127	15	25	268	44	1	2	22	93	0
	Flex	0.00	0.00	0.00	1.19	0.47	1.17	1.35	0.65	1.43	1.96	1.38	0.90	1.69	1.06	0.00
	Rigid	0.00	0.00	0.00	1.49	0.50	2.02	2.94	0.77	2.34	3.93	1.36	0.99	3.35	1.23	0.00
	GVW	4.2	3.1	5.3	29.6	19.2	36.5	58.1	34.3	56.0	76.1	59.7	63.8	85.5	23.2	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9