

Monthly WIM Distribution for 02/2011

Site Names: 00117, Cotterel WIM
 County: Cassia (16)
 Funct. Class: R Principal Arterial - Interstate
 Location: I-84 3.7 Mi. SE of Jct SH-81

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
Roadway	Num	5	1,540	940	40	143	24	2	27	2,124	132	78	53	213	108	0
	Flex	0.01	0.00	0.00	0.68	0.22	0.53	1.44	0.58	1.63	1.04	1.59	0.97	1.65	0.53	0.00
	Rigid	0.01	0.00	0.00	0.86	0.22	0.79	2.89	0.71	2.68	2.08	1.56	1.05	2.27	0.76	0.00
	GVW	5.2	3.3	5.7	27.0	17.9	28.4	51.1	35.3	64.9	70.4	59.8	62.3	81.7	31.5	0.0
NW DIR	Num	2	775	468	21	83	10	1	14	1,111	78	39	29	102	39	0
	Flex	0.01	0.00	0.00	0.76	0.17	0.49	2.39	0.72	1.63	0.99	2.08	1.26	2.18	1.00	0.00
	Rigid	0.01	0.00	0.00	0.97	0.18	0.74	4.61	0.89	2.69	1.96	2.06	1.38	2.84	1.48	0.00
	GVW	5.9	3.4	5.9	27.0	17.3	27.8	73.7	37.4	63.8	65.6	65.2	68.2	88.0	36.1	0.0
SE DIR	Num	3	766	472	20	60	13	1	13	1,013	55	39	24	111	70	0
	Flex	0.01	0.00	0.00	0.58	0.28	0.54	1.90	0.42	1.63	1.10	1.10	0.61	1.16	0.29	0.00
	Rigid	0.01	0.00	0.00	0.76	0.29	0.80	3.82	0.50	2.66	2.25	1.07	0.64	1.76	0.41	0.00
	GVW	5.5	3.2	5.6	27.1	18.6	28.2	61.8	32.7	66.2	77.0	54.3	55.1	75.7	28.8	0.0
NW 1	Num	2	521	327	19	79	10	1	14	1,096	76	38	29	101	36	0
	Flex	0.01	0.00	0.00	0.79	0.18	0.49	2.37	0.74	1.65	1.00	2.13	1.28	2.20	1.08	0.00
	Rigid	0.01	0.00	0.00	1.00	0.18	0.74	4.58	0.91	2.72	2.00	2.11	1.40	2.87	1.59	0.00
	GVW	6.2	3.5	6.5	26.9	17.3	27.7	71.0	37.7	64.1	66.0	65.8	68.0	88.4	38.3	0.0
NW 2	Num	0	254	142	2	4	0	0	1	15	2	1	1	2	3	0
	Flex	0.00	0.00	0.00	0.62	0.12	1.60	0.00	0.97	0.49	0.33	0.67	0.45	1.13	0.15	0.00
	Rigid	0.00	0.00	0.00	0.85	0.12	2.13	0.00	1.30	0.75	0.64	0.63	0.45	1.57	0.23	0.00
	GVW	14.4	3.1	4.7	29.3	16.5	87.5	0.0	79.5	45.3	45.5	58.4	56.1	76.9	10.5	0.0
SE 2	Num	1	257	153	2	6	1	0	1	50	4	5	4	10	7	0
	Flex	0.01	0.00	0.00	0.41	0.14	0.71	0.00	0.30	0.88	0.66	0.67	0.34	0.78	0.29	0.00
	Rigid	0.01	0.00	0.00	0.56	0.15	0.99	0.00	0.36	1.38	1.36	0.64	0.34	1.00	0.42	0.00
	GVW	12.0	3.0	4.5	27.4	16.4	39.3	0.0	41.4	56.3	62.4	47.5	47.5	65.9	17.4	0.0
SE 1	Num	2	509	319	18	54	12	1	12	964	51	34	19	101	63	0
	Flex	0.01	0.00	0.00	0.61	0.30	0.54	2.20	0.44	1.67	1.14	1.18	0.68	1.19	0.30	0.00
	Rigid	0.01	0.00	0.00	0.80	0.30	0.81	4.42	0.53	2.73	2.34	1.14	0.72	1.84	0.42	0.00
	GVW	5.4	3.3	6.1	27.2	18.9	28.0	64.1	33.2	66.7	78.4	55.6	57.7	76.5	30.1	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9