

## Monthly WIM Distribution for 10/2011

Site Names: 00117, Cotterel WIM  
 County: Cassia (16)  
 Funct. Class: R Principal Arterial - Interstate  
 Location: I-84 3.7 Mi. SE of Jct SH-81

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCAL	UNCLS
<b>Roadway</b>	<b>Num</b>	9	2,222	1,339	54	270	33	3	27	2,143	132	29	41	253	286	0
	<b>Flex</b>	0.01	0.00	0.00	0.86	0.19	0.39	1.26	0.47	1.68	1.11	1.63	1.09	1.76	0.32	0.00
	<b>Rigid</b>	0.01	0.00	0.00	1.04	0.19	0.58	2.45	0.57	2.76	2.29	1.60	1.20	2.22	0.45	0.00
	<b>GVW</b>	5.0	3.4	5.7	27.6	17.8	26.3	50.9	31.3	65.1	74.1	60.4	64.4	81.7	30.6	0.0
<b>NW DIR</b>	<b>Num</b>	4	1,099	626	29	167	15	1	16	1,185	70	15	25	126	56	0
	<b>Flex</b>	0.01	0.00	0.00	0.96	0.19	0.42	4.07	0.54	1.66	1.12	1.93	1.35	2.32	0.66	0.00
	<b>Rigid</b>	0.01	0.00	0.00	1.16	0.20	0.67	7.81	0.67	2.77	2.28	1.90	1.51	2.83	0.97	0.00
	<b>GVW</b>	4.8	3.5	6.0	27.3	17.5	26.6	112.0	32.8	64.0	69.9	63.8	69.4	89.3	29.2	0.0
<b>SE DIR</b>	<b>Num</b>	5	1,123	713	25	103	18	2	11	958	62	14	16	127	230	0
	<b>Flex</b>	0.01	0.00	0.00	0.75	0.19	0.36	1.16	0.38	1.70	1.10	1.26	0.65	1.21	0.24	0.00
	<b>Rigid</b>	0.01	0.00	0.00	0.90	0.19	0.49	2.34	0.43	2.74	2.31	1.23	0.68	1.65	0.33	0.00
	<b>GVW</b>	5.2	3.2	5.4	27.9	18.3	25.7	52.5	29.6	66.4	78.9	55.2	55.0	74.3	30.9	0.0
<b>NW 1</b>	<b>Num</b>	4	740	433	27	161	14	1	15	1,165	69	15	24	123	50	0
	<b>Flex</b>	0.01	0.00	0.00	1.01	0.20	0.43	4.07	0.56	1.68	1.14	1.96	1.39	2.36	0.74	0.00
	<b>Rigid</b>	0.01	0.00	0.00	1.23	0.20	0.70	7.81	0.69	2.81	2.31	1.93	1.55	2.88	1.08	0.00
	<b>GVW</b>	4.7	3.8	6.7	27.6	17.6	26.9	112.0	33.2	64.3	70.3	64.1	70.6	90.0	31.5	0.0
<b>NW 2</b>	<b>Num</b>	1	360	194	2	6	1	0	1	21	1	0	1	3	6	0
	<b>Flex</b>	0.01	0.00	0.00	0.34	0.06	0.16	0.00	0.16	0.37	0.52	2.72	1.13	0.66	0.07	0.00
	<b>Rigid</b>	0.01	0.00	0.00	0.44	0.06	0.20	0.00	0.16	0.54	1.19	2.58	1.15	0.91	0.08	0.00
	<b>GVW</b>	10.6	3.0	4.4	22.8	15.9	47.5	0.0	47.1	42.7	67.8	181.9	141.5	63.1	10.0	0.0
<b>SE 2</b>	<b>Num</b>	1	371	215	3	13	2	0	2	55	4	2	3	14	17	0
	<b>Flex</b>	0.00	0.00	0.00	0.93	0.12	0.74	2.98	0.52	1.47	1.18	1.96	0.63	1.46	0.19	0.00
	<b>Rigid</b>	0.00	0.00	0.00	1.15	0.12	0.88	7.14	0.62	2.39	2.42	1.94	0.65	1.71	0.25	0.00
	<b>GVW</b>	7.6	3.1	4.7	28.6	16.4	28.4	346.5	31.4	60.9	76.0	70.9	56.6	75.0	19.7	0.0
<b>SE 1</b>	<b>Num</b>	5	752	498	22	90	16	2	10	903	58	12	13	113	214	0
	<b>Flex</b>	0.01	0.00	0.00	0.73	0.20	0.33	1.25	0.36	1.71	1.10	1.21	0.68	1.18	0.24	0.00
	<b>Rigid</b>	0.01	0.00	0.00	0.87	0.20	0.45	2.46	0.40	2.76	2.32	1.18	0.71	1.64	0.34	0.00
	<b>GVW</b>	5.2	3.2	5.8	27.7	18.5	25.9	56.1	29.5	66.7	79.2	54.7	56.6	74.1	31.8	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9