

Idaho Transportation Department

Monthly WIM Distribution for May-2015

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	3,158	1,952	49	123	59	10	30	205	82	5	2	59	0
	Flex	.00	.00	.00	.38	.13	.46	.18	.20	.38	.37	.21	1.40	.29	0.00
	Rigid	.00	.00	.00	.38	.13	.60	.65	.21	.64	.85	.20	1.46	.50	0.00
	GVW	3.2	3.3	5.9	21.7	16.6	31.4	48.0	26.8	45.1	67.3	37.1	63.3	47.9	0.0
N	Num	3	1,587	971	20	61	18	1	13	83	49	2	1	47	0
	Flex	.00	.00	.00	.22	.11	.33	.27	.19	.35	.37	.27	.21	.24	0.00
	Rigid	.00	.00	.00	.23	.11	.46	.48	.20	.56	.80	.25	.21	.37	0.00
	GVW	.9	3.3	5.8	20.4	16.4	28.8	45.4	26.1	43.2	65.5	39.8	44.8	41.9	0.0
S	Num	6	1,570	980	28	62	41	10	17	122	32	3	2	13	0
	Flex	.00	.00	.00	.47	.15	.49	.18	.21	.40	.38	.15	1.63	.48	0.00
	Rigid	.00	.00	.00	.48	.15	.63	.66	.22	.71	.91	.14	1.69	1.05	0.00
	GVW	4.4	3.4	5.9	22.4	16.8	31.9	48.2	27.2	46.4	68.8	34.8	66.9	72.4	0.0
N Lane1	Num	3	1,587	971	20	61	18	1	13	83	49	2	1	47	0
	Flex	.00	.00	.00	.22	.11	.33	.27	.19	.35	.37	.27	.21	.24	0.00
	Rigid	.00	.00	.00	.23	.11	.46	.48	.20	.56	.80	.25	.21	.37	0.00
	GVW	.9	3.3	5.8	20.4	16.4	28.8	45.4	26.1	43.2	65.5	39.8	44.8	41.9	0.0
S Lane1	Num	6	1,570	980	28	62	41	10	17	122	32	3	2	13	0
	Flex	.00	.00	.00	.47	.15	.49	.18	.21	.40	.38	.15	1.63	.48	0.00
	Rigid	.00	.00	.00	.48	.15	.63	.66	.22	.71	.91	.14	1.69	1.05	0.00
	GVW	4.4	3.4	5.9	22.4	16.8	31.9	48.2	27.2	46.4	68.8	34.8	66.9	72.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2015

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9