

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	15	3,409	2,233	38	163	65	9	30	196	157	3	2	93	0
	Flex	.00	.00	.00	.30	.14	.39	.15	.31	.45	.45	.31	.12	.64	0.00
	Rigid	.00	.00	.00	.33	.14	.63	.49	.34	.76	1.01	.29	.13	1.11	0.00
	GVW	2.2	3.5	6.0	21.0	16.6	29.9	44.0	27.7	45.0	65.6	40.3	36.6	65.2	0.0
N	Num	7	1,736	1,110	19	82	32	3	16	93	84	2	1	44	0
	Flex	.00	.00	.00	.34	.13	.40	.08	.27	.38	.28	.42	.13	.40	0.00
	Rigid	.00	.00	.00	.37	.13	.61	.27	.29	.63	.60	.40	.12	.69	0.00
	GVW	2.3	3.4	6.0	21.7	16.5	29.9	38.9	28.0	43.4	56.5	43.7	31.0	51.6	0.0
S	Num	8	1,674	1,123	19	80	34	7	14	103	73	1	2	50	0
	Flex	.00	.00	.00	.26	.15	.40	.17	.31	.52	.65	.12	.14	.88	0.00
	Rigid	.00	.00	.00	.29	.15	.68	.55	.35	.88	1.49	.12	.15	1.52	0.00
	GVW	2.1	3.5	6.1	20.2	16.7	30.2	45.6	27.5	46.6	75.4	34.8	41.3	78.1	0.0
N Lane1	Num	7	1,736	1,110	19	82	32	3	16	93	84	2	1	44	0
	Flex	.00	.00	.00	.34	.13	.40	.08	.27	.38	.28	.42	.13	.40	0.00
	Rigid	.00	.00	.00	.37	.13	.61	.27	.29	.63	.60	.40	.12	.69	0.00
	GVW	2.3	3.4	6.0	21.7	16.5	29.9	38.9	28.0	43.4	56.5	43.7	31.0	51.6	0.0
S Lane1	Num	8	1,674	1,123	19	80	34	7	14	103	73	1	2	50	0
	Flex	.00	.00	.00	.26	.15	.40	.17	.31	.52	.65	.12	.14	.88	0.00
	Rigid	.00	.00	.00	.29	.15	.68	.55	.35	.88	1.49	.12	.15	1.52	0.00
	GVW	2.1	3.5	6.1	20.2	16.7	30.2	45.6	27.5	46.6	75.4	34.8	41.3	78.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2017

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.1 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9