

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.2 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	36	4,132	2,101	5	114	102	44	84	133	85	2	6	124	0
	Flex	.02	.00	.00	.57	.41	.44	.25	.29	.71	.62	1.14	1.21	1.48	0.00
	Rigid	.05	.00	.00	.78	.41	.75	.73	.34	1.23	1.58	1.11	2.08	2.32	0.00
	GVW	8.4	2.7	4.8	29.3	18.7	31.0	42.8	24.1	50.1	71.3	51.3	58.8	82.8	0.0
N	Num	16	2,039	1,027	3	58	46	16	42	67	47	1	4	61	0
	Flex	.03	.00	.01	.67	.41	.38	.45	.25	.60	.66	.93	1.50	1.30	0.00
	Rigid	.07	.00	.01	.97	.41	.66	1.21	.30	1.05	1.63	.89	2.83	1.96	0.00
	GVW	9.4	3.1	5.4	32.8	19.0	31.4	54.0	25.0	51.0	74.3	50.2	66.5	80.3	0.0
S	Num	20	2,093	1,074	3	56	56	28	41	66	38	1	3	63	0
	Flex	.01	.00	.00	.55	.42	.47	.16	.35	.82	.61	1.43	.74	1.67	0.00
	Rigid	.03	.00	.00	.70	.42	.81	.54	.40	1.40	1.59	1.41	.94	2.71	0.00
	GVW	7.6	2.3	4.3	26.7	18.4	30.8	37.7	23.7	48.9	68.1	59.4	44.7	85.5	0.0
N Lane1	Num	16	2,039	1,027	3	58	46	16	42	67	47	1	4	61	0
	Flex	.03	.00	.01	.67	.41	.38	.45	.25	.60	.66	.93	1.50	1.30	0.00
	Rigid	.07	.00	.01	.97	.41	.66	1.21	.30	1.05	1.63	.89	2.83	1.96	0.00
	GVW	9.4	3.1	5.4	32.8	19.0	31.4	54.0	25.0	51.0	74.3	50.2	66.5	80.3	0.0
S Lane1	Num	20	2,093	1,074	3	56	56	28	41	66	38	1	3	63	0
	Flex	.01	.00	.00	.55	.42	.47	.16	.35	.82	.61	1.43	.74	1.67	0.00
	Rigid	.03	.00	.00	.70	.42	.81	.54	.40	1.40	1.59	1.41	.94	2.71	0.00
	GVW	7.6	2.3	4.3	26.7	18.4	30.8	37.7	23.7	48.9	68.1	59.4	44.7	85.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00129
 County: Jerome
 Funct Class: R Principal Arterial - Other
 Location: US-93 1.2 Mi. N of Jct SH-25

Seasonal Factor Grp: 2
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9