

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2015

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	3,098	1,697	21	167	32	4	22	91	23	3	1	7	0
	Flex	.00	.00	.00	.73	.22	.50	.38	.47	.83	.71	1.00	.74	.79	0.00
	Rigid	.00	.00	.00	.81	.23	.80	1.24	.61	1.44	1.60	.98	.77	1.81	0.00
	GVW	4.7	3.2	6.1	25.6	17.5	30.7	56.8	31.1	53.0	75.4	45.1	58.9	80.1	0.0
E	Num	3	1,579	875	9	72	17	2	12	44	14	3	1	5	0
	Flex	.00	.00	.00	.50	.22	.62	.35	.36	.89	.79	1.49	.51	.61	0.00
	Rigid	.00	.00	.00	.56	.23	1.03	1.22	.50	1.61	1.85	1.46	.53	1.47	0.00
	GVW	4.9	3.1	6.0	23.6	16.8	34.8	56.8	32.9	55.1	82.3	58.3	54.0	70.5	0.0
W	Num	4	1,519	822	12	95	16	5	10	48	10	2	1	2	0
	Flex	.00	.00	.00	.88	.22	.43	.67	.66	.76	.61	.20	.77	1.09	0.00
	Rigid	.00	.00	.00	.97	.22	.67	1.80	.83	1.26	1.07	.18	.80	2.27	0.00
	GVW	4.8	3.3	6.3	27.1	17.9	28.9	62.6	32.5	50.7	59.3	30.4	56.0	90.3	0.0
E Lane1	Num	3	1,579	875	9	72	17	2	12	44	14	3	1	5	0
	Flex	.00	.00	.00	.50	.22	.62	.35	.36	.89	.79	1.49	.51	.61	0.00
	Rigid	.00	.00	.00	.56	.23	1.03	1.22	.50	1.61	1.85	1.46	.53	1.47	0.00
	GVW	4.9	3.1	6.0	23.6	16.8	34.8	56.8	32.9	55.1	82.3	58.3	54.0	70.5	0.0
W Lane1	Num	4	1,519	822	12	95	16	5	10	48	10	2	1	2	0
	Flex	.00	.00	.00	.88	.22	.43	.67	.66	.76	.61	.20	.77	1.09	0.00
	Rigid	.00	.00	.00	.97	.22	.67	1.80	.83	1.26	1.07	.18	.80	2.27	0.00
	GVW	4.8	3.3	6.3	27.1	17.9	28.9	62.6	32.5	50.7	59.3	30.4	56.0	90.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2015

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9