

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2019

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,081	1,844	19	122	19	1	16	80	19	0	0	11	0
	Flex	.00	.00	.00	.23	.12	.43	.13	.35	.48	.66	0.00	0.00	.63	0.00
	Rigid	.00	.00	.00	.26	.12	.59	.31	.38	.82	1.42	0.00	0.00	1.05	0.00
	GVW	1.4	3.6	5.9	19.6	15.2	29.2	37.8	30.3	45.8	71.9	0.0	0.0	61.0	0.0
E	Num	1	1,582	953	9	89	10	1	9	42	9	0	0	7	0
	Flex	.00	.00	.00	.32	.13	.63	.20	.44	.68	.88	0.00	0.00	.79	0.00
	Rigid	.00	.00	.00	.36	.13	.88	.34	.47	1.14	1.90	0.00	0.00	1.43	0.00
	GVW	1.9	4.1	6.5	21.2	14.9	34.3	37.6	33.2	52.3	83.9	0.0	0.0	68.9	0.0
W	Num	2	1,499	892	10	34	10	1	7	39	11	0	0	5	0
	Flex	.00	.00	.00	.16	.11	.19	.12	.17	.28	.47	0.00	0.00	.41	0.00
	Rigid	.00	.00	.00	.17	.11	.26	.38	.18	.47	.97	0.00	0.00	.64	0.00
	GVW	1.2	3.0	5.2	18.2	16.1	23.4	40.6	25.1	38.9	61.3	0.0	0.0	54.6	0.0
E Lane1	Num	1	1,582	953	9	89	10	1	9	42	9	0	0	7	0
	Flex	.00	.00	.00	.32	.13	.63	.20	.44	.68	.88	0.00	0.00	.79	0.00
	Rigid	.00	.00	.00	.36	.13	.88	.34	.47	1.14	1.90	0.00	0.00	1.43	0.00
	GVW	1.9	4.1	6.5	21.2	14.9	34.3	37.6	33.2	52.3	83.9	0.0	0.0	68.9	0.0
W Lane1	Num	2	1,499	892	10	34	10	1	7	39	11	0	0	5	0
	Flex	.00	.00	.00	.16	.11	.19	.12	.17	.28	.47	0.00	0.00	.41	0.00
	Rigid	.00	.00	.00	.17	.11	.26	.38	.18	.47	.97	0.00	0.00	.64	0.00
	GVW	1.2	3.0	5.2	18.2	16.1	23.4	40.6	25.1	38.9	61.3	0.0	0.0	54.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2019

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9