

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,404	1,763	17	138	25	1	21	88	21	1	1	13	0
	Flex	.00	.00	.00	.22	.10	.30	.28	.28	.47	.44	.18	.67	.58	0.00
	Rigid	.00	.00	.00	.24	.10	.44	.76	.31	.79	.98	.17	.70	.93	0.00
	GVW	.9	3.4	6.1	20.8	15.7	26.6	50.0	29.3	46.4	62.5	34.7	64.7	61.0	0.0
E	Num	2	1,292	903	9	85	11	1	12	42	10	1	1	8	0
	Flex	.00	.00	.00	.23	.09	.50	.35	.30	.57	.71	.15	.67	.34	0.00
	Rigid	.00	.00	.00	.24	.09	.76	.88	.32	.95	1.61	.14	.70	.60	0.00
	GVW	1.1	4.0	6.6	21.0	15.0	31.9	51.5	29.7	49.5	77.2	33.7	64.7	51.9	0.0
W	Num	1	1,192	859	8	52	14	1	10	46	11	1	0	5	0
	Flex	.00	.00	.00	.20	.12	.15	.13	.23	.38	.17	.16	0.00	.93	0.00
	Rigid	.00	.00	.00	.21	.11	.20	.52	.28	.67	.34	.15	0.00	1.45	0.00
	GVW	.7	2.9	5.5	19.8	16.6	22.7	47.3	26.1	43.7	44.6	33.2	0.0	73.8	0.0
E Lane1	Num	2	1,292	903	9	85	11	1	12	42	10	1	1	8	0
	Flex	.00	.00	.00	.23	.09	.50	.35	.30	.57	.71	.15	.67	.34	0.00
	Rigid	.00	.00	.00	.24	.09	.76	.88	.32	.95	1.61	.14	.70	.60	0.00
	GVW	1.1	4.0	6.6	21.0	15.0	31.9	51.5	29.7	49.5	77.2	33.7	64.7	51.9	0.0
W Lane1	Num	1	1,192	859	8	52	14	1	10	46	11	1	0	5	0
	Flex	.00	.00	.00	.20	.12	.15	.13	.23	.38	.17	.16	0.00	.93	0.00
	Rigid	.00	.00	.00	.21	.11	.20	.52	.28	.67	.34	.15	0.00	1.45	0.00
	GVW	.7	2.9	5.5	19.8	16.6	22.7	47.3	26.1	43.7	44.6	33.2	0.0	73.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9