

# Idaho Transportation Department

## Monthly WIM Distribution for May-2020

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	2,739	1,933	17	172	20	2	19	78	20	0	2	13	0
	Flex	.00	.00	.00	.35	.09	.54	.49	.33	.74	.68	0.00	.28	.74	0.00
	Rigid	.00	.00	.00	.37	.09	.82	1.11	.39	1.37	1.59	0.00	.27	1.58	0.00
	GVW	1.0	3.6	6.1	21.0	15.3	30.6	51.4	28.7	49.0	68.7	0.0	38.4	65.1	0.0
E	Num	2	1,436	978	9	126	11	2	11	39	9	0	1	6	0
	Flex	.00	.00	.00	.47	.09	.80	.66	.39	.98	1.12	0.00	.66	.99	0.00
	Rigid	.00	.00	.00	.51	.09	1.24	1.37	.45	1.78	2.66	0.00	.66	2.30	0.00
	GVW	1.0	4.1	6.9	22.8	15.1	34.9	54.7	30.2	53.2	83.8	0.0	62.1	73.9	0.0
W	Num	2	1,303	954	8	46	9	1	8	40	11	0	1	7	0
	Flex	.00	.00	.00	.21	.10	.22	.17	.22	.50	.26	0.00	.06	.44	0.00
	Rigid	.00	.00	.00	.22	.10	.33	.65	.26	.97	.57	0.00	.06	.69	0.00
	GVW	.9	3.0	5.4	19.0	16.1	25.2	45.6	25.5	45.0	54.1	0.0	24.9	53.9	0.0
E Lane1	Num	2	1,436	978	9	126	11	2	11	39	9	0	1	6	0
	Flex	.00	.00	.00	.47	.09	.80	.66	.39	.98	1.12	0.00	.66	.99	0.00
	Rigid	.00	.00	.00	.51	.09	1.24	1.37	.45	1.78	2.66	0.00	.66	2.30	0.00
	GVW	1.0	4.1	6.9	22.8	15.1	34.9	54.7	30.2	53.2	83.8	0.0	62.1	73.9	0.0
W Lane1	Num	2	1,303	954	8	46	9	1	8	40	11	0	1	7	0
	Flex	.00	.00	.00	.21	.10	.22	.17	.22	.50	.26	0.00	.06	.44	0.00
	Rigid	.00	.00	.00	.22	.10	.33	.65	.26	.97	.57	0.00	.06	.69	0.00
	GVW	.9	3.0	5.4	19.0	16.1	25.2	45.6	25.5	45.0	54.1	0.0	24.9	53.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2020

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9