

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2022

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	3,665	1,706	0	44	34	10	43	113	27	14	5	16	0
	Flex	.00	.00	.00	0.00	.36	.35	.62	.60	.89	.47	2.21	3.32	1.34	0.00
	Rigid	.00	.00	.00	0.00	.34	.63	1.21	.66	1.72	1.11	2.17	4.06	2.12	0.00
	GVW	1.9	2.6	4.6	0.0	20.3	33.2	56.2	36.7	60.0	69.1	67.3	81.8	88.0	0.0
E	Num	0	1,829	889	0	19	16	5	19	62	16	6	2	7	0
	Flex	0.00	.00	.00	0.00	.37	.42	.59	.57	1.06	.54	1.17	.12	.69	0.00
	Rigid	0.00	.00	.00	0.00	.36	.80	1.30	.63	2.09	1.31	1.11	.15	1.16	0.00
	GVW	0.0	2.7	4.7	0.0	21.3	35.1	58.5	35.3	62.5	73.9	58.2	42.6	75.8	0.0
W	Num	1	1,836	817	0	25	18	5	24	51	11	8	3	9	0
	Flex	.00	.00	.00	0.00	.35	.29	.66	.62	.69	.37	2.99	5.45	1.85	0.00
	Rigid	.00	.00	.00	0.00	.33	.48	1.12	.69	1.26	.81	2.96	6.66	2.87	0.00
	GVW	1.9	2.4	4.4	0.0	19.5	31.6	53.9	37.8	57.0	62.0	74.1	108.0	97.5	0.0
E Lane1	Num	0	1,829	889	0	19	16	5	19	62	16	6	2	7	0
	Flex	0.00	.00	.00	0.00	.37	.42	.59	.57	1.06	.54	1.17	.12	.69	0.00
	Rigid	0.00	.00	.00	0.00	.36	.80	1.30	.63	2.09	1.31	1.11	.15	1.16	0.00
	GVW	0.0	2.7	4.7	0.0	21.3	35.1	58.5	35.3	62.5	73.9	58.2	42.6	75.8	0.0
W Lane1	Num	1	1,836	817	0	25	18	5	24	51	11	8	3	9	0
	Flex	.00	.00	.00	0.00	.35	.29	.66	.62	.69	.37	2.99	5.45	1.85	0.00
	Rigid	.00	.00	.00	0.00	.33	.48	1.12	.69	1.26	.81	2.96	6.66	2.87	0.00
	GVW	1.9	2.4	4.4	0.0	19.5	31.6	53.9	37.8	57.0	62.0	74.1	108.0	97.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2022

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9