

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	3,810	1,922	2	65	35	5	49	110	31	4	2	17	0
	Flex	.03	.00	.00	.38	.27	.33	.30	.22	.59	.47	2.87	1.07	.91	0.00
	Rigid	.06	.00	.00	.49	.26	.51	.78	.27	1.06	1.08	2.87	2.09	1.51	0.00
	GVW	2.2	2.5	4.2	22.3	16.7	28.5	49.5	21.5	48.4	63.8	67.0	56.0	74.5	0.0
E	Num	6	1,960	982	1	31	19	3	24	52	16	4	2	9	0
	Flex	.00	.00	.00	.57	.26	.33	.25	.17	.49	.47	1.03	.77	.68	0.00
	Rigid	.00	.00	.00	.70	.25	.51	.72	.19	.84	1.10	.99	.90	1.08	0.00
	GVW	1.2	2.6	4.4	30.4	17.7	30.8	49.6	21.1	49.3	68.7	50.8	55.0	73.1	0.0
W	Num	3	1,851	940	2	34	16	4	25	58	15	3	1	8	0
	Flex	.06	.00	.00	.33	.28	.33	.31	.27	.66	.45	3.52	1.26	1.04	0.00
	Rigid	.14	.00	.00	.43	.27	.52	.80	.35	1.24	1.00	3.54	2.60	1.75	0.00
	GVW	3.7	2.4	4.1	17.3	15.9	26.0	49.6	21.9	47.5	58.0	73.7	63.1	71.6	0.0
E Lane1	Num	6	1,960	982	1	31	19	3	24	52	16	4	2	9	0
	Flex	.00	.00	.00	.57	.26	.33	.25	.17	.49	.47	1.03	.77	.68	0.00
	Rigid	.00	.00	.00	.70	.25	.51	.72	.19	.84	1.10	.99	.90	1.08	0.00
	GVW	1.2	2.6	4.4	30.4	17.7	30.8	49.6	21.1	49.3	68.7	50.8	55.0	73.1	0.0
W Lane1	Num	3	1,851	940	2	34	16	4	25	58	15	3	1	8	0
	Flex	.06	.00	.00	.33	.28	.33	.31	.27	.66	.45	3.52	1.26	1.04	0.00
	Rigid	.14	.00	.00	.43	.27	.52	.80	.35	1.24	1.00	3.54	2.60	1.75	0.00
	GVW	3.7	2.4	4.1	17.3	15.9	26.0	49.6	21.9	47.5	58.0	73.7	63.1	71.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2022

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9