

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2023

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,551	1,787	3	64	29	3	33	79	21	4	2	12	0
	Flex	.08	.00	.00	.49	.37	.39	.45	.23	.68	.52	3.06	.81	.96	0.00
	Rigid	.18	.00	.00	.79	.37	.65	.91	.25	1.27	1.21	3.07	1.63	1.67	0.00
	GVW	11.1	2.4	4.1	30.9	18.9	33.1	55.6	25.2	54.5	65.8	72.5	67.0	73.3	0.0
E	Num	2	1,816	927	1	31	16	2	15	37	10	1	1	6	0
	Flex	.00	.00	.00	.41	.32	.37	.34	.22	.69	.59	1.08	.40	.53	0.00
	Rigid	.00	.00	.00	.61	.32	.62	.61	.23	1.30	1.39	1.05	.62	.88	0.00
	GVW	3.7	2.4	4.1	28.3	18.1	32.6	48.2	24.9	53.9	65.8	51.7	55.9	67.1	0.0
W	Num	1	1,735	860	2	33	13	2	18	42	10	3	1	6	0
	Flex	.18	.00	.00	.62	.41	.43	.55	.25	.67	.45	3.31	.94	1.60	0.00
	Rigid	.39	.00	.00	1.04	.41	.70	1.18	.28	1.23	1.04	3.32	1.92	2.80	0.00
	GVW	19.0	2.4	4.2	35.0	19.6	33.7	59.9	25.6	54.9	66.5	75.4	70.3	81.5	0.0
E Lane1	Num	2	1,816	927	1	31	16	2	15	37	10	1	1	6	0
	Flex	.00	.00	.00	.41	.32	.37	.34	.22	.69	.59	1.08	.40	.53	0.00
	Rigid	.00	.00	.00	.61	.32	.62	.61	.23	1.30	1.39	1.05	.62	.88	0.00
	GVW	3.7	2.4	4.1	28.3	18.1	32.6	48.2	24.9	53.9	65.8	51.7	55.9	67.1	0.0
W Lane1	Num	1	1,735	860	2	33	13	2	18	42	10	3	1	6	0
	Flex	.18	.00	.00	.62	.41	.43	.55	.25	.67	.45	3.31	.94	1.60	0.00
	Rigid	.39	.00	.00	1.04	.41	.70	1.18	.28	1.23	1.04	3.32	1.92	2.80	0.00
	GVW	19.0	2.4	4.2	35.0	19.6	33.7	59.9	25.6	54.9	66.5	75.4	70.3	81.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2023

Site names: 00133  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9