

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	13	3,771	2,109	5	78	52	6	46	88	17	3	3	11	0
	Flex	.06	.00	.00	1.74	.50	.73	.52	.29	1.16	.70	4.34	1.59	2.83	0.00
	Rigid	.13	.00	.00	2.31	.53	1.29	1.12	.32	2.20	1.63	4.75	2.56	4.07	0.00
	GVW	9.9	2.4	4.2	25.9	17.8	33.4	53.1	22.2	52.9	66.3	68.7	59.9	76.7	0.0
E	Num	7	1,946	1,089	2	38	25	2	22	44	8	1	2	5	0
	Flex	.09	.00	.00	.37	.45	.62	.49	.37	1.00	.80	1.60	.54	.85	0.00
	Rigid	.20	.00	.00	.42	.46	1.03	1.11	.40	1.87	1.85	1.61	.75	1.27	0.00
	GVW	10.3	2.5	4.3	18.8	18.1	34.2	50.2	23.0	52.4	68.8	55.4	40.6	58.9	0.0
W	Num	6	1,825	1,019	3	40	27	5	24	44	8	2	1	6	0
	Flex	.02	.00	.00	2.33	.54	.85	.73	.22	1.23	.55	7.46	2.79	4.80	0.00
	Rigid	.04	.00	.00	3.12	.59	1.58	1.46	.25	2.33	1.33	8.39	4.51	6.77	0.00
	GVW	9.5	2.4	4.2	29.6	17.5	32.7	61.5	21.6	52.5	62.7	82.2	80.1	96.6	0.0
E Lane1	Num	7	1,946	1,089	2	38	25	2	22	44	8	1	2	5	0
	Flex	.09	.00	.00	.37	.45	.62	.49	.37	1.00	.80	1.60	.54	.85	0.00
	Rigid	.20	.00	.00	.42	.46	1.03	1.11	.40	1.87	1.85	1.61	.75	1.27	0.00
	GVW	10.3	2.5	4.3	18.8	18.1	34.2	50.2	23.0	52.4	68.8	55.4	40.6	58.9	0.0
W Lane1	Num	6	1,825	1,019	3	40	27	5	24	44	8	2	1	6	0
	Flex	.02	.00	.00	2.33	.54	.85	.73	.22	1.23	.55	7.46	2.79	4.80	0.00
	Rigid	.04	.00	.00	3.12	.59	1.58	1.46	.25	2.33	1.33	8.39	4.51	6.77	0.00
	GVW	9.5	2.4	4.2	29.6	17.5	32.7	61.5	21.6	52.5	62.7	82.2	80.1	96.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00133

County: Twin Falls

Funct Class: R Minor Arterial - Other

Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1

Daily Factor Grp: 2

Axle Factor Grp: All_Class_Sites

Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9