

Idaho Transportation Department

Monthly WIM Distribution for Aug-2024

Site names: 00133
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	12	3,707	2,193	8	87	72	8	53	100	22	1	4	32	0
	Flex	.05	.00	.00	1.12	.34	.50	.45	.22	.82	.78	3.64	.82	1.84	0.00
	Rigid	.10	.00	.00	1.51	.34	.86	.87	.24	1.52	1.92	3.99	1.35	2.63	0.00
	GVW	10.0	2.4	4.1	27.3	16.2	29.0	42.1	20.9	49.4	67.7	65.3	50.4	70.4	0.0
E	Num	6	1,929	1,132	4	43	33	5	26	50	12	1	2	18	0
	Flex	.06	.00	.00	.41	.30	.32	.24	.23	.63	.64	.86	.39	.74	0.00
	Rigid	.12	.00	.00	.42	.29	.53	.62	.24	1.15	1.49	.83	.57	1.16	0.00
	GVW	10.3	2.4	4.2	21.4	16.5	28.7	41.2	21.9	50.0	68.9	49.8	43.8	63.2	0.0
W	Num	6	1,779	1,061	4	45	39	5	28	50	11	1	3	15	0
	Flex	.03	.00	.00	1.72	.37	.64	.60	.20	1.01	1.10	6.08	1.36	2.98	0.00
	Rigid	.07	.00	.00	2.33	.38	1.13	1.10	.23	1.89	2.92	6.73	2.30	4.13	0.00
	GVW	9.2	2.4	4.0	30.7	15.7	29.3	45.0	19.9	48.6	73.1	78.4	58.8	76.0	0.0
E Lane1	Num	6	1,929	1,132	4	43	33	5	26	50	12	1	2	18	0
	Flex	.06	.00	.00	.41	.30	.32	.24	.23	.63	.64	.86	.39	.74	0.00
	Rigid	.12	.00	.00	.42	.29	.53	.62	.24	1.15	1.49	.83	.57	1.16	0.00
	GVW	10.3	2.4	4.2	21.4	16.5	28.7	41.2	21.9	50.0	68.9	49.8	43.8	63.2	0.0
W Lane1	Num	6	1,779	1,061	4	45	39	5	28	50	11	1	3	15	0
	Flex	.03	.00	.00	1.72	.37	.64	.60	.20	1.01	1.10	6.08	1.36	2.98	0.00
	Rigid	.07	.00	.00	2.33	.38	1.13	1.10	.23	1.89	2.92	6.73	2.30	4.13	0.00
	GVW	9.2	2.4	4.0	30.7	15.7	29.3	45.0	19.9	48.6	73.1	78.4	58.8	76.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Aug-2024

Site names: 00133
County: Twin Falls
Funct Class: R Minor Arterial - Other
Location: US-30 5.0 Mi. W of Stevens Ave

Seasonal Factor Grp: 1
Daily Factor Grp: 2
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 5

		UNCLS
--	--	-------

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9