

Idaho Transportation Department

Monthly WIM Distribution for Jan-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	506	313	14	373	8	1	17	415	15	1	1	27	0
	Flex	.00	.00	.00	1.19	.85	.71	2.09	1.05	2.34	1.50	4.40	2.39	2.35	0.00
	Rigid	.00	.00	.00	1.49	.90	1.22	2.95	1.21	4.54	3.32	4.64	2.90	4.67	0.00
	GVW	.3	5.2	7.2	27.5	21.2	35.4	67.6	34.5	78.2	81.2	75.6	85.6	101.1	0.0
SE	Num	0	109	61	8	293	4	1	12	246	8	1	1	8	0
	Flex	0.00	.02	.01	1.33	1.03	.80	.08	1.29	2.46	1.67	5.45	2.45	2.45	0.00
	Rigid	0.00	.01	.01	1.64	1.09	1.29	.20	1.47	4.81	3.51	5.82	2.98	4.78	0.00
	GVW	0.0	7.7	7.1	28.1	22.7	35.3	31.2	34.5	79.8	83.4	82.8	86.6	95.5	0.0
NW	Num	1	397	252	6	81	4	1	6	169	8	1	1	18	0
	Flex	.00	.00	.00	1.05	.23	.72	2.22	.56	2.19	1.58	3.14	2.80	2.38	0.00
	Rigid	.00	.00	.00	1.33	.25	1.35	3.12	.69	4.24	3.73	3.19	3.44	4.75	0.00
	GVW	.3	4.9	7.4	26.6	15.6	36.2	70.9	33.8	76.1	81.0	69.4	87.2	104.2	0.0
NW Lane1	Num	1	397	252	6	81	4	1	6	169	8	1	1	18	0
	Flex	.00	.00	.00	1.05	.23	.72	2.22	.56	2.19	1.58	3.14	2.80	2.38	0.00
	Rigid	.00	.00	.00	1.33	.25	1.35	3.12	.69	4.24	3.73	3.19	3.44	4.75	0.00
	GVW	.3	4.9	7.4	26.6	15.6	36.2	70.9	33.8	76.1	81.0	69.4	87.2	104.2	0.0
SE Lane1	Num	0	109	61	8	293	4	1	12	246	8	1	1	8	0
	Flex	0.00	.02	.01	1.33	1.03	.80	.08	1.29	2.46	1.67	5.45	2.45	2.45	0.00
	Rigid	0.00	.01	.01	1.64	1.09	1.29	.20	1.47	4.81	3.51	5.82	2.98	4.78	0.00
	GVW	0.0	7.7	7.1	28.1	22.7	35.3	31.2	34.5	79.8	83.4	82.8	86.6	95.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9