

Idaho Transportation Department

Monthly WIM Distribution for Mar-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	842	628	15	141	6	1	11	489	18	1	1	21	0
	Flex	.00	.00	.00	1.53	.50	.85	2.70	1.13	4.07	2.10	7.42	4.92	2.56	0.00
	Rigid	.00	.00	.00	2.07	.55	1.72	4.49	1.62	8.72	5.16	8.44	6.87	5.37	0.00
	GVW	1.3	4.3	6.7	29.7	17.4	35.1	77.0	35.9	88.8	90.0	80.7	95.2	102.5	0.0
SE	Num	2	397	333	8	59	3	1	6	281	9	1	1	6	0
	Flex	.00	.00	.00	1.76	.90	1.30	1.44	1.80	5.51	3.22	8.68	6.59	2.83	0.00
	Rigid	.00	.00	.00	2.49	.99	2.78	4.24	2.66	12.15	7.89	9.94	9.76	6.59	0.00
	GVW	1.1	3.5	6.1	30.4	19.2	37.5	72.9	39.9	98.2	96.8	84.2	104.7	93.3	0.0
NW	Num	1	444	295	7	82	4	1	5	208	10	1	1	15	0
	Flex	.00	.00	.00	1.24	.22	.51	2.81	.48	2.13	1.18	2.54	1.60	2.43	0.00
	Rigid	.00	.00	.00	1.54	.23	.90	4.48	.57	4.10	2.86	2.50	1.85	4.82	0.00
	GVW	1.5	4.9	7.4	28.6	16.2	32.9	77.2	31.3	75.9	84.4	71.3	75.8	103.6	0.0
NW Lane1	Num	1	444	295	7	82	4	1	5	208	10	1	1	15	0
	Flex	.00	.00	.00	1.24	.22	.51	2.81	.48	2.13	1.18	2.54	1.60	2.43	0.00
	Rigid	.00	.00	.00	1.54	.23	.90	4.48	.57	4.10	2.86	2.50	1.85	4.82	0.00
	GVW	1.5	4.9	7.4	28.6	16.2	32.9	77.2	31.3	75.9	84.4	71.3	75.8	103.6	0.0
SE Lane1	Num	2	397	333	8	59	3	1	6	281	9	1	1	6	0
	Flex	.00	.00	.00	1.76	.90	1.30	1.44	1.80	5.51	3.22	8.68	6.59	2.83	0.00
	Rigid	.00	.00	.00	2.49	.99	2.78	4.24	2.66	12.15	7.89	9.94	9.76	6.59	0.00
	GVW	1.1	3.5	6.1	30.4	19.2	37.5	72.9	39.9	98.2	96.8	84.2	104.7	93.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9