

Idaho Transportation Department

Monthly WIM Distribution for May-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	998	733	17	193	8	1	15	451	15	1	1	16	0
	Flex	.00	.00	.00	1.61	.38	1.17	1.74	.93	3.96	2.37	2.85	4.37	2.49	0.00
	Rigid	.00	.00	.00	2.12	.41	2.50	3.92	1.33	8.46	5.68	2.93	5.96	5.43	0.00
	GVW	3.0	4.3	6.9	29.8	17.4	37.6	68.2	34.3	87.8	89.2	64.6	94.5	100.2	0.0
SE	Num	1	474	393	8	79	4	1	7	252	8	1	1	4	0
	Flex	.00	.00	.00	1.62	.67	1.74	1.28	1.33	5.46	3.45	2.44	5.98	3.87	0.00
	Rigid	.00	.00	.00	2.21	.74	3.77	3.45	2.02	11.99	8.33	2.50	8.36	9.49	0.00
	GVW	3.4	3.7	6.3	28.3	18.5	42.0	67.3	37.3	97.8	96.6	61.8	101.4	113.9	0.0
NW	Num	3	524	340	9	115	4	1	8	199	7	1	1	12	0
	Flex	.00	.00	.00	1.53	.19	.91	1.68	.56	2.03	1.26	6.59	2.78	2.11	0.00
	Rigid	.00	.00	.00	1.93	.20	1.85	3.63	.69	3.90	2.94	6.89	3.22	4.31	0.00
	GVW	3.3	4.8	7.5	30.8	16.7	35.9	66.9	31.6	74.6	81.6	92.5	83.9	96.7	0.0
NW Lane1	Num	3	524	340	9	115	4	1	8	199	7	1	1	12	0
	Flex	.00	.00	.00	1.53	.19	.91	1.68	.56	2.03	1.26	6.59	2.78	2.11	0.00
	Rigid	.00	.00	.00	1.93	.20	1.85	3.63	.69	3.90	2.94	6.89	3.22	4.31	0.00
	GVW	3.3	4.8	7.5	30.8	16.7	35.9	66.9	31.6	74.6	81.6	92.5	83.9	96.7	0.0
SE Lane1	Num	1	474	393	8	79	4	1	7	252	8	1	1	4	0
	Flex	.00	.00	.00	1.62	.67	1.74	1.28	1.33	5.46	3.45	2.44	5.98	3.87	0.00
	Rigid	.00	.00	.00	2.21	.74	3.77	3.45	2.02	11.99	8.33	2.50	8.36	9.49	0.00
	GVW	3.4	3.7	6.3	28.3	18.5	42.0	67.3	37.3	97.8	96.6	61.8	101.4	113.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2015

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9