

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2017

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	821	643	17	47	10	1	11	392	16	1	1	20	0
	Flex	.00	.00	.00	.43	.17	.35	.17	.27	.77	.55	1.31	.76	.67	0.00
	Rigid	.00	.00	.00	.44	.16	.44	.45	.29	1.30	1.09	1.28	.79	1.16	0.00
	GVW	4.0	3.1	5.5	23.0	17.2	27.5	44.8	29.4	61.1	66.3	54.9	54.6	73.1	0.0
SE	Num	2	416	326	9	23	5	1	6	239	9	1	1	10	0
	Flex	.00	.00	.00	.39	.16	.28	.20	.20	.81	.54	2.44	.20	.54	0.00
	Rigid	.00	.00	.00	.40	.16	.33	.54	.21	1.41	1.07	2.38	.20	.95	0.00
	GVW	4.2	3.0	5.4	22.7	16.9	25.8	46.8	27.1	63.5	67.6	71.2	43.6	65.4	0.0
NW	Num	2	405	318	9	25	5	1	6	153	7	1	1	11	0
	Flex	.00	.00	.00	.45	.17	.44	.14	.30	.69	.57	.18	1.45	.79	0.00
	Rigid	.00	.00	.00	.46	.17	.55	.27	.33	1.13	1.15	.17	1.51	1.34	0.00
	GVW	3.2	3.2	5.6	22.5	17.4	29.2	44.1	31.4	57.3	65.9	38.5	71.2	79.9	0.0
NW Lane1	Num	2	405	318	9	25	5	1	6	153	7	1	1	11	0
	Flex	.00	.00	.00	.45	.17	.44	.14	.30	.69	.57	.18	1.45	.79	0.00
	Rigid	.00	.00	.00	.46	.17	.55	.27	.33	1.13	1.15	.17	1.51	1.34	0.00
	GVW	3.2	3.2	5.6	22.5	17.4	29.2	44.1	31.4	57.3	65.9	38.5	71.2	79.9	0.0
SE Lane1	Num	2	416	326	9	23	5	1	6	239	9	1	1	10	0
	Flex	.00	.00	.00	.39	.16	.28	.20	.20	.81	.54	2.44	.20	.54	0.00
	Rigid	.00	.00	.00	.40	.16	.33	.54	.21	1.41	1.07	2.38	.20	.95	0.00
	GVW	4.2	3.0	5.4	22.7	16.9	25.8	46.8	27.1	63.5	67.6	71.2	43.6	65.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2017

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9