

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	21	1,336	995	23	164	45	6	19	446	19	1	2	15	0
	Flex	.00	.00	.00	.99	.24	.75	.58	.46	1.54	.86	.77	.86	1.24	0.00
	Rigid	.00	.00	.00	1.27	.25	1.32	1.45	.51	2.86	1.77	.73	.95	2.68	0.00
	GVW	3.0	3.5	6.2	28.2	17.9	33.8	52.9	30.2	65.8	68.6	51.8	56.5	85.2	0.0
SE	Num	10	657	484	10	92	23	4	10	259	9	1	1	8	0
	Flex	.00	.00	.00	1.18	.24	1.09	.51	.48	1.96	.99	.63	1.51	1.47	0.00
	Rigid	.00	.00	.00	1.67	.25	2.01	1.50	.54	3.74	2.06	.59	1.84	3.31	0.00
	GVW	2.5	3.5	6.1	29.1	17.7	38.0	53.4	29.5	69.6	68.9	49.9	63.9	86.5	0.0
NW	Num	10	680	510	13	72	22	2	9	187	10	1	2	7	0
	Flex	.00	.00	.00	.86	.24	.47	.94	.43	1.05	.76	.86	1.27	.94	0.00
	Rigid	.00	.00	.00	.97	.26	.70	1.97	.47	1.80	1.55	.82	1.40	1.89	0.00
	GVW	3.3	3.4	6.2	27.2	18.1	30.5	56.3	30.4	60.9	70.1	52.0	61.0	83.2	0.0
NW Lane1	Num	10	680	510	13	72	22	2	9	187	10	1	2	7	0
	Flex	.00	.00	.00	.86	.24	.47	.94	.43	1.05	.76	.86	1.27	.94	0.00
	Rigid	.00	.00	.00	.97	.26	.70	1.97	.47	1.80	1.55	.82	1.40	1.89	0.00
	GVW	3.3	3.4	6.2	27.2	18.1	30.5	56.3	30.4	60.9	70.1	52.0	61.0	83.2	0.0
SE Lane1	Num	10	657	484	10	92	23	4	10	259	9	1	1	8	0
	Flex	.00	.00	.00	1.18	.24	1.09	.51	.48	1.96	.99	.63	1.51	1.47	0.00
	Rigid	.00	.00	.00	1.67	.25	2.01	1.50	.54	3.74	2.06	.59	1.84	3.31	0.00
	GVW	2.5	3.5	6.1	29.1	17.7	38.0	53.4	29.5	69.6	68.9	49.9	63.9	86.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9