

Idaho Transportation Department

Monthly WIM Distribution for Sep-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	9	1,166	949	23	106	25	5	15	481	24	1	2	18	0
	Flex	.00	.00	.00	.60	.19	.32	.37	.23	.77	.62	.53	.36	.53	0.00
	Rigid	.00	.00	.00	.75	.21	.55	.83	.30	1.45	1.40	.51	.38	1.14	0.00
	GVW	3.3	3.4	6.0	22.6	16.9	26.9	46.1	25.1	55.0	58.0	43.8	49.0	68.9	0.0
SE	Num	4	572	463	11	67	13	3	8	281	13	1	2	10	0
	Flex	.00	.00	.00	.77	.15	.46	.40	.30	1.12	.97	.76	.52	.58	0.00
	Rigid	.00	.00	.00	1.02	.16	.82	.96	.40	2.16	2.22	.75	.54	1.30	0.00
	GVW	2.8	3.6	6.1	23.4	16.9	29.2	47.3	26.1	60.2	63.6	47.2	53.8	68.1	0.0
NW	Num	6	594	485	12	40	12	3	7	200	11	1	1	8	0
	Flex	.00	.00	.00	.44	.24	.17	.27	.12	.33	.22	.25	.17	.38	0.00
	Rigid	.00	.00	.00	.50	.27	.24	.49	.12	.55	.44	.24	.18	.74	0.00
	GVW	3.6	3.3	5.9	21.7	16.8	24.6	44.7	23.6	47.6	50.4	37.2	41.9	67.1	0.0
NW Lane1	Num	6	594	485	12	40	12	3	7	200	11	1	1	8	0
	Flex	.00	.00	.00	.44	.24	.17	.27	.12	.33	.22	.25	.17	.38	0.00
	Rigid	.00	.00	.00	.50	.27	.24	.49	.12	.55	.44	.24	.18	.74	0.00
	GVW	3.6	3.3	5.9	21.7	16.8	24.6	44.7	23.6	47.6	50.4	37.2	41.9	67.1	0.0
SE Lane1	Num	4	572	463	11	67	13	3	8	281	13	1	2	10	0
	Flex	.00	.00	.00	.77	.15	.46	.40	.30	1.12	.97	.76	.52	.58	0.00
	Rigid	.00	.00	.00	1.02	.16	.82	.96	.40	2.16	2.22	.75	.54	1.30	0.00
	GVW	2.8	3.6	6.1	23.4	16.9	29.2	47.3	26.1	60.2	63.6	47.2	53.8	68.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2017

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9