

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	992	797	16	47	19	3	14	438	18	1	2	20	0
	Flex	.00	.00	.00	.16	.09	.14	.10	.11	.34	.22	.62	.29	.25	0.00
	Rigid	.00	.00	.00	.15	.09	.21	.30	.12	.58	.42	.58	.31	.45	0.00
	GVW	4.4	3.2	5.6	17.9	16.5	24.3	41.1	23.5	50.4	52.5	52.3	49.6	60.2	0.0
SE	Num	1	509	393	8	22	9	3	8	276	9	1	2	10	0
	Flex	.00	.00	.00	.17	.09	.16	.09	.14	.36	.22	.73	.33	.21	0.00
	Rigid	.00	.00	.00	.17	.10	.26	.31	.15	.63	.43	.69	.34	.41	0.00
	GVW	5.1	3.2	5.6	18.4	16.2	25.1	41.6	25.8	52.3	53.2	54.4	52.1	57.7	0.0
NW	Num	1	483	404	8	25	10	1	7	162	9	1	1	11	0
	Flex	.00	.00	.00	.13	.09	.11	.14	.09	.29	.21	.51	.26	.28	0.00
	Rigid	.00	.00	.00	.13	.08	.15	.37	.09	.49	.41	.47	.26	.50	0.00
	GVW	3.4	3.2	5.5	17.1	16.6	22.8	42.7	22.0	46.9	51.4	50.1	39.9	62.3	0.0
NW Lane1	Num	1	483	404	8	25	10	1	7	162	9	1	1	11	0
	Flex	.00	.00	.00	.13	.09	.11	.14	.09	.29	.21	.51	.26	.28	0.00
	Rigid	.00	.00	.00	.13	.08	.15	.37	.09	.49	.41	.47	.26	.50	0.00
	GVW	3.4	3.2	5.5	17.1	16.6	22.8	42.7	22.0	46.9	51.4	50.1	39.9	62.3	0.0
SE Lane1	Num	1	509	393	8	22	9	3	8	276	9	1	2	10	0
	Flex	.00	.00	.00	.17	.09	.16	.09	.14	.36	.22	.73	.33	.21	0.00
	Rigid	.00	.00	.00	.17	.10	.26	.31	.15	.63	.43	.69	.34	.41	0.00
	GVW	5.1	3.2	5.6	18.4	16.2	25.1	41.6	25.8	52.3	53.2	54.4	52.1	57.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9