

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2018

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	905	712	15	39	13	1	12	378	17	2	2	21	0
	Flex	.00	.00	.00	.17	.17	.13	.11	.12	.35	.22	.43	.26	.26	0.00
	Rigid	.00	.00	.00	.18	.18	.19	.24	.13	.60	.45	.40	.28	.47	0.00
	GVW	4.5	3.2	5.5	18.6	16.1	23.2	35.8	23.5	51.0	56.0	41.8	47.1	59.8	0.0
SE	Num	1	464	351	7	19	6	2	6	233	8	1	2	10	0
	Flex	.00	.00	.00	.15	.08	.16	.09	.14	.39	.22	.55	.33	.23	0.00
	Rigid	.00	.00	.00	.15	.07	.24	.31	.16	.68	.45	.51	.33	.42	0.00
	GVW	4.8	3.2	5.5	18.2	15.6	24.6	40.2	24.7	53.5	55.2	49.8	51.3	57.2	0.0
NW	Num	1	441	360	8	20	7	1	7	144	9	1	1	11	0
	Flex	.00	.00	.00	.18	.24	.12	.10	.09	.28	.21	.11	.18	.30	0.00
	Rigid	.00	.00	.00	.19	.27	.15	.16	.10	.47	.43	.10	.20	.54	0.00
	GVW	4.0	3.2	5.5	18.7	16.5	22.3	30.9	22.3	47.1	56.6	26.3	41.0	63.5	0.0
NW Lane1	Num	1	441	360	8	20	7	1	7	144	9	1	1	11	0
	Flex	.00	.00	.00	.18	.24	.12	.10	.09	.28	.21	.11	.18	.30	0.00
	Rigid	.00	.00	.00	.19	.27	.15	.16	.10	.47	.43	.10	.20	.54	0.00
	GVW	4.0	3.2	5.5	18.7	16.5	22.3	30.9	22.3	47.1	56.6	26.3	41.0	63.5	0.0
SE Lane1	Num	1	464	351	7	19	6	2	6	233	8	1	2	10	0
	Flex	.00	.00	.00	.15	.08	.16	.09	.14	.39	.22	.55	.33	.23	0.00
	Rigid	.00	.00	.00	.15	.07	.24	.31	.16	.68	.45	.51	.33	.42	0.00
	GVW	4.8	3.2	5.5	18.2	15.6	24.6	40.2	24.7	53.5	55.2	49.8	51.3	57.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2018

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9