

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	5	1,219	1,112	16	80	11	3	15	402	21	1	2	18	0
	Flex	.00	.00	.00	.29	.11	.36	.27	.43	.74	.46	.71	.35	.52	0.00
	Rigid	.00	.00	.00	.34	.12	.55	.59	.54	1.36	1.00	.67	.42	1.00	0.00
	GVW	1.7	3.3	5.9	21.8	17.1	28.1	44.5	28.1	57.4	61.8	53.1	47.4	65.3	0.0
SE	Num	2	633	536	5	47	5	2	7	255	11	0	2	13	0
	Flex	.00	.00	.00	.25	.09	.31	.88	.18	.76	.39	0.00	.32	.48	0.00
	Rigid	.00	.00	.00	.26	.09	.44	1.47	.19	1.40	.77	0.00	.34	.85	0.00
	GVW	.9	3.4	6.0	20.1	16.7	24.6	51.6	25.8	58.1	55.9	0.0	45.5	61.6	0.0
NW	Num	4	586	576	11	33	6	3	8	146	11	1	1	5	0
	Flex	.00	.00	.00	.31	.14	.37	.28	.64	.65	.55	.71	.45	.61	0.00
	Rigid	.00	.00	.00	.38	.15	.58	.59	.82	1.19	1.26	.67	.68	1.42	0.00
	GVW	2.0	3.3	5.7	22.5	17.7	30.6	44.8	28.5	55.4	68.4	53.1	50.4	73.7	0.0
NW Lane1	Num	4	586	576	11	33	6	3	8	146	11	1	1	5	0
	Flex	.00	.00	.00	.31	.14	.37	.28	.64	.65	.55	.71	.45	.61	0.00
	Rigid	.00	.00	.00	.38	.15	.58	.59	.82	1.19	1.26	.67	.68	1.42	0.00
	GVW	2.0	3.3	5.7	22.5	17.7	30.6	44.8	28.5	55.4	68.4	53.1	50.4	73.7	0.0
SE Lane1	Num	2	633	536	5	47	5	2	7	255	11	0	2	13	0
	Flex	.00	.00	.00	.25	.09	.31	.88	.18	.76	.39	0.00	.32	.48	0.00
	Rigid	.00	.00	.00	.26	.09	.44	1.47	.19	1.40	.77	0.00	.34	.85	0.00
	GVW	.9	3.4	6.0	20.1	16.7	24.6	51.6	25.8	58.1	55.9	0.0	45.5	61.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9