

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2022

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,263	969	5	57	23	5	54	444	55	2	4	47	0
	Flex	.22	.00	.00	.89	.34	.34	.75	.18	1.13	.63	1.48	1.23	1.10	0.00
	Rigid	.49	.00	.00	1.19	.34	.56	1.91	.23	2.11	1.49	1.77	1.77	1.97	0.00
	GVW	9.4	2.5	4.3	44.2	18.4	30.7	59.3	23.8	66.1	73.7	62.7	66.5	89.2	0.0
SE	Num	2	630	494	3	30	11	2	25	272	34	2	2	18	0
	Flex	.02	.00	.00	.87	.33	.40	.53	.20	1.26	.59	1.41	.87	.90	0.00
	Rigid	.04	.01	.00	1.11	.33	.65	1.19	.26	2.40	1.39	1.69	1.45	1.53	0.00
	GVW	3.3	2.5	4.4	42.1	18.8	32.4	56.8	25.7	70.1	72.7	61.2	66.7	76.6	0.0
NW	Num	2	633	476	3	27	13	3	29	171	22	1	2	28	0
	Flex	.66	.00	.00	1.00	.34	.31	1.09	.17	.94	.71	2.40	2.10	1.23	0.00
	Rigid	1.51	.00	.00	1.37	.33	.50	2.78	.21	1.68	1.67	2.71	2.45	2.24	0.00
	GVW	20.0	2.5	4.1	45.4	18.0	29.6	62.5	22.5	59.7	75.8	77.5	65.4	96.7	0.0
NW Lane1	Num	2	633	476	3	27	13	3	29	171	22	1	2	28	0
	Flex	.66	.00	.00	1.00	.34	.31	1.09	.17	.94	.71	2.40	2.10	1.23	0.00
	Rigid	1.51	.00	.00	1.37	.33	.50	2.78	.21	1.68	1.67	2.71	2.45	2.24	0.00
	GVW	20.0	2.5	4.1	45.4	18.0	29.6	62.5	22.5	59.7	75.8	77.5	65.4	96.7	0.0
SE Lane1	Num	2	630	494	3	30	11	2	25	272	34	2	2	18	0
	Flex	.02	.00	.00	.87	.33	.40	.53	.20	1.26	.59	1.41	.87	.90	0.00
	Rigid	.04	.01	.00	1.11	.33	.65	1.19	.26	2.40	1.39	1.69	1.45	1.53	0.00
	GVW	3.3	2.5	4.4	42.1	18.8	32.4	56.8	25.7	70.1	72.7	61.2	66.7	76.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2022

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 2  
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9