

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2023

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,155	714	4	49	12	4	34	319	64	2	3	35	0
	Flex	.07	.00	.00	1.01	.35	.34	.74	.19	1.13	.76	.90	.72	.99	0.00
	Rigid	.14	.00	.00	1.40	.35	.53	1.67	.22	2.11	1.84	.97	1.22	1.86	0.00
	GVW	11.3	2.6	4.1	46.5	18.5	29.8	58.9	25.0	65.5	81.4	52.4	65.0	86.4	0.0
SE	Num	1	551	363	2	25	6	3	15	186	49	1	2	14	0
	Flex	.00	.01	.00	.94	.31	.28	.68	.24	1.25	.77	1.13	.85	.83	0.00
	Rigid	.01	.01	.00	1.30	.31	.43	1.48	.28	2.34	1.89	1.08	1.40	1.53	0.00
	GVW	4.1	2.6	4.3	45.7	18.2	29.4	58.1	27.0	68.2	80.5	56.5	70.3	75.4	0.0
NW	Num	1	604	352	3	24	6	2	19	132	15	1	1	21	0
	Flex	.12	.00	.00	.88	.38	.39	.81	.16	1.01	.77	.80	.56	1.09	0.00
	Rigid	.25	.00	.00	1.28	.38	.62	2.05	.19	1.86	1.81	.96	1.08	2.06	0.00
	GVW	13.5	2.6	3.9	46.9	18.4	29.9	64.3	23.7	61.7	83.3	51.2	58.6	93.5	0.0
NW Lane1	Num	1	604	352	3	24	6	2	19	132	15	1	1	21	0
	Flex	.12	.00	.00	.88	.38	.39	.81	.16	1.01	.77	.80	.56	1.09	0.00
	Rigid	.25	.00	.00	1.28	.38	.62	2.05	.19	1.86	1.81	.96	1.08	2.06	0.00
	GVW	13.5	2.6	3.9	46.9	18.4	29.9	64.3	23.7	61.7	83.3	51.2	58.6	93.5	0.0
SE Lane1	Num	1	551	363	2	25	6	3	15	186	49	1	2	14	0
	Flex	.00	.01	.00	.94	.31	.28	.68	.24	1.25	.77	1.13	.85	.83	0.00
	Rigid	.01	.01	.00	1.30	.31	.43	1.48	.28	2.34	1.89	1.08	1.40	1.53	0.00
	GVW	4.1	2.6	4.3	45.7	18.2	29.4	58.1	27.0	68.2	80.5	56.5	70.3	75.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2023

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9