

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2023

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,571	1,145	7	67	27	6	69	403	49	3	3	40	0
	Flex	.08	.00	.00	1.02	.40	.32	1.06	.16	1.16	.82	.92	.38	1.09	0.00
	Rigid	.17	.00	.00	1.36	.40	.54	2.41	.19	2.17	1.96	.89	.54	2.12	0.00
	GVW	10.8	2.5	4.4	44.0	18.7	28.5	61.6	22.2	64.9	78.0	51.8	46.7	87.5	0.0
SE	Num	2	788	582	4	37	11	2	32	247	29	2	2	17	0
	Flex	.11	.00	.00	.95	.37	.27	.97	.16	1.29	.68	1.32	.64	.86	0.00
	Rigid	.23	.00	.00	1.22	.37	.42	1.68	.18	2.46	1.56	1.27	.94	1.53	0.00
	GVW	12.2	2.5	4.5	43.1	18.7	28.6	63.8	23.0	69.0	73.0	57.0	54.8	75.5	0.0
NW	Num	2	783	563	3	31	16	4	36	156	20	2	2	23	0
	Flex	.05	.00	.00	1.00	.44	.39	1.16	.17	.98	1.00	.70	.17	1.26	0.00
	Rigid	.09	.00	.00	1.37	.45	.67	2.78	.20	1.77	2.46	.68	.22	2.56	0.00
	GVW	9.8	2.5	4.4	42.5	18.6	29.0	62.2	21.7	58.3	84.9	48.6	40.0	95.7	0.0
NW Lane1	Num	2	783	563	3	31	16	4	36	156	20	2	2	23	0
	Flex	.05	.00	.00	1.00	.44	.39	1.16	.17	.98	1.00	.70	.17	1.26	0.00
	Rigid	.09	.00	.00	1.37	.45	.67	2.78	.20	1.77	2.46	.68	.22	2.56	0.00
	GVW	9.8	2.5	4.4	42.5	18.6	29.0	62.2	21.7	58.3	84.9	48.6	40.0	95.7	0.0
SE Lane1	Num	2	788	582	4	37	11	2	32	247	29	2	2	17	0
	Flex	.11	.00	.00	.95	.37	.27	.97	.16	1.29	.68	1.32	.64	.86	0.00
	Rigid	.23	.00	.00	1.22	.37	.42	1.68	.18	2.46	1.56	1.27	.94	1.53	0.00
	GVW	12.2	2.5	4.5	43.1	18.7	28.6	63.8	23.0	69.0	73.0	57.0	54.8	75.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2023

Site names: 00134  
 County: Bear Lake  
 Funct Class: R Principal Arterial - Other  
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9