

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,328	918	7	64	21	4	55	387	43	3	4	28	0
	Flex	.11	.00	.00	.88	.28	.45	.62	.13	1.10	.61	1.08	.44	1.09	0.00
	Rigid	.24	.00	.00	1.14	.28	.78	1.19	.15	2.06	1.45	1.03	.64	2.28	0.00
	GVW	14.2	2.4	4.2	39.1	17.2	30.5	57.3	22.4	64.7	73.5	55.1	48.3	92.4	0.0
SE	Num	2	664	465	5	33	10	2	26	239	29	2	3	10	0
	Flex	.12	.00	.00	.69	.26	.35	.66	.13	1.22	.57	1.24	.31	.80	0.00
	Rigid	.27	.00	.00	.88	.26	.55	1.21	.15	2.34	1.38	1.19	.43	1.75	0.00
	GVW	16.9	2.4	4.3	35.2	17.5	31.2	60.4	23.0	68.4	73.4	55.1	45.2	79.4	0.0
NW	Num	2	664	453	3	31	11	3	28	148	15	2	1	18	0
	Flex	.09	.00	.00	.97	.29	.56	.66	.13	.91	.70	.72	.90	1.24	0.00
	Rigid	.19	.00	.00	1.25	.29	1.01	1.33	.15	1.63	1.59	.68	1.42	2.55	0.00
	GVW	13.2	2.3	4.2	41.8	16.9	30.7	60.6	21.9	58.1	74.0	50.1	59.6	99.1	0.0
NW Lane1	Num	2	664	453	3	31	11	3	28	148	15	2	1	18	0
	Flex	.09	.00	.00	.97	.29	.56	.66	.13	.91	.70	.72	.90	1.24	0.00
	Rigid	.19	.00	.00	1.25	.29	1.01	1.33	.15	1.63	1.59	.68	1.42	2.55	0.00
	GVW	13.2	2.3	4.2	41.8	16.9	30.7	60.6	21.9	58.1	74.0	50.1	59.6	99.1	0.0
SE Lane1	Num	2	664	465	5	33	10	2	26	239	29	2	3	10	0
	Flex	.12	.00	.00	.69	.26	.35	.66	.13	1.22	.57	1.24	.31	.80	0.00
	Rigid	.27	.00	.00	.88	.26	.55	1.21	.15	2.34	1.38	1.19	.43	1.75	0.00
	GVW	16.9	2.4	4.3	35.2	17.5	31.2	60.4	23.0	68.4	73.4	55.1	45.2	79.4	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2024

Site names: 00134

County: Bear Lake

Funct Class: R Principal Arterial - Other

Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4

Daily Factor Grp: 3

Axle Factor Grp: All_Class_Sites

Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9