Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,767	1,267	8	66	26	7	73	388	40	4	5	30	0
	Flex	.09	.00	.00	.89	.35	.32	.44	.12	1.10	.67	.76	.86	1.28	0.00
	Rigid	.19	.00	.00	1.23	.36	.50	1.04	.14	2.08	1.53	.73	1.21	2.37	0.00
	GVW	10.1	2.5	4.4	38.0	18.1	28.6	57.6	20.8	63.9	71.7	48.8	52.1	89.5	0.0
SE	Num	2	889	645	4	35	9	5	33	240	22	2	3	13	0
	Flex	.16	.00	.00	.62	.34	.32	.64	.13	1.19	.51	1.26	.38	1.18	0.00
	Rigid	.34	.00	.00	.81	.34	.52	1.42	.14	2.28	1.16	1.21	.47	2.32	0.00
	GVW	14.2	2.5	4.5	35.3	18.7	29.0	64.9	21.0	67.8	67.0	56.8	45.8	85.4	0.0
NW	Num	2	879	623	4	31	17	3	40	148	18	3	3	17	0
	Flex	.02	.00	.00	1.01	.37	.32	.45	.12	1.01	.89	.36	1.57	1.33	0.00
	Rigid	.03	.00	.00	1.43	.38	.49	1.05	.13	1.82	2.05	.34	2.35	2.39	0.00
	GVW	7.0	2.5	4.4	39.2	17.5	28.2	55.2	20.8	57.5	78.2	42.8	61.1	91.8	0.0
NW Lane1	Num	2	879	623	4	31	17	3	40	148	18	3	3	17	0
	Flex	.02	.00	.00	1.01	.37	.32	.45	.12	1.01	.89	.36	1.57	1.33	0.00
	Rigid	.03	.00	.00	1.43	.38	.49	1.05	.13	1.82	2.05	.34	2.35	2.39	0.00
	GVW	7.0	2.5	4.4	39.2	17.5	28.2	55.2	20.8	57.5	78.2	42.8	61.1	91.8	0.0
SE Lane1	Num	2	889	645	4	35	9	5	33	240	22	2	3	13	0
	Flex	.16	.00	.00	.62	.34	.32	.64	.13	1.19	.51	1.26	.38	1.18	0.00
	Rigid	.34	.00	.00	.81	.34	.52	1.42	.14	2.28	1.16	1.21	.47	2.32	0.00
	GVW	14.2	2.5	4.5	35.3	18.7	29.0	64.9	21.0	67.8	67.0	56.8	45.8	85.4	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 08/09/2024 8:34 AM

Idaho Transportation Department

Monthly WIM Distribution for Jul-2024

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 08/09/2024 8:34 AM