Idaho Transportation Department

Monthly WIM Distribution for Sep-2024

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,403	1,103	11	72	21	4	60	439	45	3	4	38	0
	Flex	.16	.00	.00	1.12	.39	.36	.71	.14	1.17	.73	1.23	.57	1.22	0.00
	Rigid	.36	.00	.00	1.43	.40	.61	1.59	.16	2.22	1.71	1.20	.85	2.21	0.00
	GVW	12.6	2.4	4.3	39.4	18.2	28.7	54.4	22.0	65.1	75.4	53.9	48.6	89.6	0.0
SE	Num	2	693	562	6	38	8	2	28	283	22	2	2	17	0
	Flex	.14	.00	.00	1.10	.35	.33	.43	.13	1.33	.67	1.69	.33	.99	0.00
	Rigid	.30	.00	.00	1.41	.36	.51	.76	.15	2.57	1.59	1.64	.46	1.87	0.00
	GVW	9.2	2.4	4.4	40.3	18.3	29.3	46.0	22.6	69.7	72.5	60.0	46.2	81.2	0.0
NW	Num	2	710	541	5	35	13	3	32	156	22	2	3	21	0
	Flex	.18	.00	.00	1.11	.42	.38	.97	.16	.90	.79	.70	.89	1.43	0.00
	Rigid	.40	.00	.00	1.47	.43	.65	2.29	.18	1.63	1.82	.67	1.39	2.55	0.00
	GVW	16.0	2.4	4.2	38.2	18.0	28.3	60.1	21.6	56.7	78.2	47.5	56.0	96.2	0.0
NW Lane1	Num	2	710	541	5	35	13	3	32	156	22	2	3	21	0
	Flex	.18	.00	.00	1.11	.42	.38	.97	.16	.90	.79	.70	.89	1.43	0.00
	Rigid	.40	.00	.00	1.47	.43	.65	2.29	.18	1.63	1.82	.67	1.39	2.55	0.00
	GVW	16.0	2.4	4.2	38.2	18.0	28.3	60.1	21.6	56.7	78.2	47.5	56.0	96.2	0.0
SE Lane1	Num	2	693	562	6	38	8	2	28	283	22	2	2	17	0
	Flex	.14	.00	.00	1.10	.35	.33	.43	.13	1.33	.67	1.69	.33	.99	0.00
	Rigid	.30	.00	.00	1.41	.36	.51	.76	.15	2.57	1.59	1.64	.46	1.87	0.00
	GVW	9.2	2.4	4.4	40.3	18.3	29.3	46.0	22.6	69.7	72.5	60.0	46.2	81.2	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 10/03/2024 1:39 PM

Idaho Transportation Department

Monthly WIM Distribution for Sep-2024

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 10/03/2024 1:39 PM