

Idaho Transportation Department

Monthly WIM Distribution for Oct-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,246	1,033	8	62	24	3	50	425	34	3	2	22	0
	Flex	.23	.00	.00	1.00	.36	.39	.76	.16	1.17	.80	1.11	.44	1.21	0.00
	Rigid	.49	.00	.00	1.28	.36	.66	1.81	.19	2.20	1.91	1.06	.55	2.21	0.00
	GVW	15.6	2.4	4.3	39.0	18.1	30.5	59.3	23.3	66.1	78.5	55.4	49.2	92.7	0.0
SE	Num	2	626	528	5	33	10	1	22	275	18	2	2	9	0
	Flex	.24	.00	.00	1.43	.37	.35	.65	.19	1.35	.80	1.49	.57	.92	0.00
	Rigid	.51	.00	.00	1.78	.37	.56	1.36	.22	2.59	1.93	1.44	.71	1.96	0.00
	GVW	17.0	2.5	4.4	41.8	18.4	30.5	58.4	24.5	70.9	78.3	60.4	52.2	87.5	0.0
NW	Num	2	620	506	4	30	14	3	28	150	17	2	2	14	0
	Flex	.25	.00	.00	.82	.34	.42	.89	.14	.88	.83	.74	.46	1.39	0.00
	Rigid	.54	.00	.00	1.06	.34	.73	2.22	.16	1.57	1.96	.71	.65	2.40	0.00
	GVW	16.0	2.4	4.1	38.0	17.6	30.7	61.8	22.4	57.5	79.3	49.3	49.2	97.1	0.0
NW Lane1	Num	2	620	506	4	30	14	3	28	150	17	2	2	14	0
	Flex	.25	.00	.00	.82	.34	.42	.89	.14	.88	.83	.74	.46	1.39	0.00
	Rigid	.54	.00	.00	1.06	.34	.73	2.22	.16	1.57	1.96	.71	.65	2.40	0.00
	GVW	16.0	2.4	4.1	38.0	17.6	30.7	61.8	22.4	57.5	79.3	49.3	49.2	97.1	0.0
SE Lane1	Num	2	626	528	5	33	10	1	22	275	18	2	2	9	0
	Flex	.24	.00	.00	1.43	.37	.35	.65	.19	1.35	.80	1.49	.57	.92	0.00
	Rigid	.51	.00	.00	1.78	.37	.56	1.36	.22	2.59	1.93	1.44	.71	1.96	0.00
	GVW	17.0	2.5	4.4	41.8	18.4	30.5	58.4	24.5	70.9	78.3	60.4	52.2	87.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Oct-2024

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		UNCLS
--	--	-------

Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9