

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,095	819	7	51	18	3	37	365	31	2	3	34	0
	Flex	.27	.00	.00	.74	.29	.35	.62	.15	1.12	.67	1.48	.45	1.17	0.00
	Rigid	.58	.00	.00	.94	.29	.58	1.50	.17	2.13	1.55	1.44	.54	2.02	0.00
	GVW	17.8	2.5	4.1	35.9	18.0	30.2	55.4	24.3	66.7	77.7	60.1	51.6	90.3	0.0
SE	Num	1	550	421	4	26	7	2	17	228	17	1	2	14	0
	Flex	.41	.00	.00	.82	.30	.38	.43	.16	1.31	.68	1.17	.34	.56	0.00
	Rigid	.87	.00	.00	1.01	.30	.64	.78	.18	2.52	1.59	1.13	.38	1.00	0.00
	GVW	22.4	2.5	4.3	35.7	18.5	31.7	50.1	25.7	71.5	76.3	55.0	48.6	69.8	0.0
NW	Num	2	544	397	3	24	11	2	20	138	14	1	1	19	0
	Flex	.22	.00	.00	.62	.28	.36	.67	.13	.82	.67	1.59	.82	1.60	0.00
	Rigid	.46	.00	.00	.82	.28	.59	1.83	.15	1.46	1.54	1.55	1.12	2.73	0.00
	GVW	15.8	2.4	3.9	34.5	17.4	30.0	56.0	22.5	58.5	79.8	62.0	64.4	104.8	0.0
NW Lane1	Num	2	544	397	3	24	11	2	20	138	14	1	1	19	0
	Flex	.22	.00	.00	.62	.28	.36	.67	.13	.82	.67	1.59	.82	1.60	0.00
	Rigid	.46	.00	.00	.82	.28	.59	1.83	.15	1.46	1.54	1.55	1.12	2.73	0.00
	GVW	15.8	2.4	3.9	34.5	17.4	30.0	56.0	22.5	58.5	79.8	62.0	64.4	104.8	0.0
SE Lane1	Num	1	550	421	4	26	7	2	17	228	17	1	2	14	0
	Flex	.41	.00	.00	.82	.30	.38	.43	.16	1.31	.68	1.17	.34	.56	0.00
	Rigid	.87	.00	.00	1.01	.30	.64	.78	.18	2.52	1.59	1.13	.38	1.00	0.00
	GVW	22.4	2.5	4.3	35.7	18.5	31.7	50.1	25.7	71.5	76.3	55.0	48.6	69.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2024

Site names: 00134

County: Bear Lake

Funct Class: R Principal Arterial - Other

Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4

Daily Factor Grp: 3

Axle Factor Grp: All_Class_Sites

Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9