

Idaho Transportation Department

Monthly WIM Distribution for Feb-2025

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	941	748	6	45	19	3	31	317	35	3	3	31	0
	Flex	.14	.00	.00	.84	.29	.29	.19	.14	1.03	.51	1.15	.23	.97	0.00
	Rigid	.30	.00	.00	1.13	.29	.46	.43	.15	1.94	1.16	1.10	.30	1.81	0.00
	GVW	16.0	2.5	3.9	41.4	17.7	29.2	40.4	23.5	66.0	73.5	55.4	44.8	90.5	0.0
SE	Num	2	468	382	4	24	8	3	15	206	20	2	2	11	0
	Flex	.22	.00	.00	.85	.31	.38	.17	.17	1.15	.49	1.11	.18	.87	0.00
	Rigid	.47	.00	.00	1.16	.30	.62	.35	.19	2.20	1.11	1.06	.22	1.79	0.00
	GVW	18.4	2.5	4.1	41.7	18.3	32.2	38.8	25.6	69.3	69.7	54.7	43.3	79.2	0.0
NW	Num	3	473	366	3	22	11	2	16	110	15	2	1	19	0
	Flex	.09	.00	.00	.80	.27	.25	.22	.11	.82	.53	1.05	.39	1.04	0.00
	Rigid	.20	.00	.00	1.01	.26	.38	.50	.12	1.47	1.22	1.01	.54	1.89	0.00
	GVW	14.6	2.4	3.6	38.8	17.0	28.2	42.1	21.7	59.8	77.8	52.6	50.3	97.9	0.0
NW Lane1	Num	3	473	366	3	22	11	2	16	110	15	2	1	19	0
	Flex	.09	.00	.00	.80	.27	.25	.22	.11	.82	.53	1.05	.39	1.04	0.00
	Rigid	.20	.00	.00	1.01	.26	.38	.50	.12	1.47	1.22	1.01	.54	1.89	0.00
	GVW	14.6	2.4	3.6	38.8	17.0	28.2	42.1	21.7	59.8	77.8	52.6	50.3	97.9	0.0
SE Lane1	Num	2	468	382	4	24	8	3	15	206	20	2	2	11	0
	Flex	.22	.00	.00	.85	.31	.38	.17	.17	1.15	.49	1.11	.18	.87	0.00
	Rigid	.47	.00	.00	1.16	.30	.62	.35	.19	2.20	1.11	1.06	.22	1.79	0.00
	GVW	18.4	2.5	4.1	41.7	18.3	32.2	38.8	25.6	69.3	69.7	54.7	43.3	79.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2025

Site names: 00134
 County: Bear Lake
 Funct Class: R Principal Arterial - Other
 Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9