Idaho Transportation Department

Monthly WIM Distribution for Mar-2025

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,091	766	5	49	16	2	34	359	36	3	3	32	0
	Flex	.08	.00	.00	.69	.26	.30	.67	.15	1.05	.58	.95	.32	1.09	0.00
	Rigid	.17	.00	.00	.85	.26	.48	1.49	.17	1.96	1.33	.91	.40	2.01	0.00
	GVW	13.3	2.4	3.9	37.6	17.3	29.8	57.6	23.8	65.9	74.4	53.0	46.8	92.6	0.0
SE	Num	1	543	388	3	26	7	1	15	229	21	2	2	11	0
	Flex	.10	.00	.00	.63	.25	.35	.37	.14	1.15	.49	1.06	.24	.89	0.00
	Rigid	.21	.00	.00	.74	.25	.55	.84	.16	2.21	1.12	1.02	.27	1.62	0.00
	GVW	16.6	2.4	4.1	36.4	17.4	32.0	53.8	24.7	69.4	69.2	53.6	44.6	77.0	0.0
NW	Num	2	548	378	2	23	9	2	19	129	16	2	1	21	0
	Flex	.04	.00	.00	.81	.27	.29	.86	.14	.87	.69	.78	.95	1.20	0.00
	Rigid	.08	.00	.00	1.08	.26	.46	1.77	.17	1.54	1.60	.74	1.32	2.23	0.00
	GVW	10.1	2.3	3.8	41.6	17.1	28.8	60.5	22.8	59.8	81.1	50.9	58.8	101.5	0.0
NW Lane1	Num	2	548	378	2	23	9	2	19	129	16	2	1	21	0
	Flex	.04	.00	.00	.81	.27	.29	.86	.14	.87	.69	.78	.95	1.20	0.00
	Rigid	.08	.00	.00	1.08	.26	.46	1.77	.17	1.54	1.60	.74	1.32	2.23	0.00
	GVW	10.1	2.3	3.8	41.6	17.1	28.8	60.5	22.8	59.8	81.1	50.9	58.8	101.5	0.0
SE Lane1	Num	1	543	388	3	26	7	1	15	229	21	2	2	11	0
	Flex	.10	.00	.00	.63	.25	.35	.37	.14	1.15	.49	1.06	.24	.89	0.00
	Rigid	.21	.00	.00	.74	.25	.55	.84	.16	2.21	1.12	1.02	.27	1.62	0.00
	GVW	16.6	2.4	4.1	36.4	17.4	32.0	53.8	24.7	69.4	69.2	53.6	44.6	77.0	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 04/06/2025 2:16 PM

Idaho Transportation Department

Monthly WIM Distribution for Mar-2025

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 04/06/2025 2:16 PM