Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,167	842	7	56	19	3	41	366	34	4	7	29	0
	Flex	.14	.00	.00	.95	.30	.36	1.03	.14	1.09	.70	.64	.21	1.20	0.00
	Rigid	.30	.00	.00	1.21	.30	.59	1.93	.16	2.04	1.69	.61	.25	2.22	0.00
	GVW	16.4	2.4	4.1	36.6	17.9	29.9	61.2	23.2	65.1	78.6	49.5	42.3	91.4	0.0
SE	Num	2	583	425	3	29	8	2	19	235	21	2	6	10	0
	Flex	.16	.00	.00	1.16	.27	.37	.97	.15	1.19	.64	.61	.18	.89	0.00
	Rigid	.34	.00	.00	1.50	.27	.59	1.73	.17	2.28	1.55	.58	.19	1.95	0.00
	GVW	19.1	2.4	4.2	40.9	17.9	31.6	63.9	24.3	68.7	77.4	47.9	41.1	77.3	0.0
NW	Num	2	584	417	4	26	12	2	21	132	13	2	2	19	0
	Flex	.11	.00	.00	.81	.34	.36	1.23	.14	.93	.79	.71	.49	1.40	0.00
	Rigid	.24	.00	.00	.96	.34	.61	2.33	.15	1.66	1.90	.68	.76	2.51	0.00
	GVW	15.4	2.3	4.0	32.6	17.8	29.5	62.7	22.2	58.5	80.5	51.5	52.3	100.0	0.0
NW Lane1	Num	2	584	417	4	26	12	2	21	132	13	2	2	19	0
	Flex	.11	.00	.00	.81	.34	.36	1.23	.14	.93	.79	.71	.49	1.40	0.00
	Rigid	.24	.00	.00	.96	.34	.61	2.33	.15	1.66	1.90	.68	.76	2.51	0.00
	GVW	15.4	2.3	4.0	32.6	17.8	29.5	62.7	22.2	58.5	80.5	51.5	52.3	100.0	0.0
SE Lane1	Num	2	583	425	3	29	8	2	19	235	21	2	6	10	0
	Flex	.16	.00	.00	1.16	.27	.37	.97	.15	1.19	.64	.61	.18	.89	0.00
	Rigid	.34	.00	.00	1.50	.27	.59	1.73	.17	2.28	1.55	.58	.19	1.95	0.00
	GVW	19.1	2.4	4.2	40.9	17.9	31.6	63.9	24.3	68.7	77.4	47.9	41.1	77.3	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 05/08/2025 10:58 AM

Idaho Transportation Department

Monthly WIM Distribution for Apr-2025

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 05/08/2025 10:58 AM