Idaho Transportation Department

Monthly WIM Distribution for Aug-2025

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,593	1,201	9	73	26	4	72	407	41	3	10	36	0
	Flex	.06	.00	.00	.95	.33	.37	.49	.14	1.08	.80	.83	.24	1.40	0.00
	Rigid	.14	.00	.00	1.16	.33	.60	.93	.15	2.04	1.91	.81	.30	2.47	0.00
	GVW	10.4	2.5	4.4	36.4	17.6	30.1	50.5	21.6	63.9	81.0	50.1	42.0	90.3	0.0
SE	Num	2	792	610	4	39	11	3	35	257	22	2	9	14	0
	Flex	.07	.00	.00	1.05	.30	.36	.51	.15	1.21	.76	1.02	.20	1.19	0.00
	Rigid	.16	.00	.00	1.29	.30	.57	.92	.17	2.32	1.89	.99	.23	2.16	0.00
	GVW	9.0	2.5	4.5	40.7	17.6	30.5	50.6	23.0	68.4	82.1	52.1	41.4	86.6	0.0
NW	Num	3	800	591	5	34	16	2	37	150	19	2	2	22	0
	Flex	.06	.00	.00	.85	.38	.37	.46	.13	.91	.82	.61	.46	1.53	0.00
	Rigid	.14	.00	.00	1.02	.38	.61	1.07	.14	1.63	1.89	.58	.65	2.66	0.00
	GVW	11.9	2.5	4.4	32.9	17.7	30.1	54.5	20.3	56.2	79.5	48.8	45.0	92.9	0.0
NW Lane1	Num	3	800	591	5	34	16	2	37	150	19	2	2	22	0
	Flex	.06	.00	.00	.85	.38	.37	.46	.13	.91	.82	.61	.46	1.53	0.00
	Rigid	.14	.00	.00	1.02	.38	.61	1.07	.14	1.63	1.89	.58	.65	2.66	0.00
	GVW	11.9	2.5	4.4	32.9	17.7	30.1	54.5	20.3	56.2	79.5	48.8	45.0	92.9	0.0
SE Lane1	Num	2	792	610	4	39	11	3	35	257	22	2	9	14	0
	Flex	.07	.00	.00	1.05	.30	.36	.51	.15	1.21	.76	1.02	.20	1.19	0.00
	Rigid	.16	.00	.00	1.29	.30	.57	.92	.17	2.32	1.89	.99	.23	2.16	0.00
	GVW	9.0	2.5	4.5	40.7	17.6	30.5	50.6	23.0	68.4	82.1	52.1	41.4	86.6	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 09/02/2025 6:56 AM

Idaho Transportation Department

Monthly WIM Distribution for Aug-2025

Site names: 00134
County: Bear Lake
Funct Class: R Principal Arterial - Other
Location: US-30 200 Ft. S of Smith Ln

Seasonal Factor Grp: 4
Daily Factor Grp: 3
Axle Factor Grp: All_Class_Sites
Growth Factor Grp: 6

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9

Created 09/02/2025 6:56 AM