

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	17	1,684	1,165	8	73	54	12	99	72	47	1	4	15	0
	Flex	.08	.00	.01	.49	.52	.48	.21	.27	1.01	1.49	.77	1.40	1.71	0.00
	Rigid	.19	.00	.01	.69	.58	.82	.58	.33	1.82	3.59	1.01	3.11	3.21	0.00
	GVW	8.4	2.6	5.0	24.3	16.7	28.2	36.3	19.6	48.8	73.2	35.8	66.7	81.5	0.0
N	Num	15	850	526	5	34	20	8	49	35	28	1	3	9	0
	Flex	.05	.00	.01	.67	.90	.84	.23	.43	1.51	2.39	1.03	1.77	2.08	0.00
	Rigid	.12	.01	.02	.89	1.02	1.42	.60	.53	2.82	5.74	1.34	3.99	3.88	0.00
	GVW	6.7	3.2	6.1	21.2	19.0	29.5	33.4	22.7	52.3	80.8	44.9	72.5	79.8	0.0
S	Num	3	833	638	3	40	33	4	50	37	19	1	2	6	0
	Flex	.27	.00	.00	.38	.16	.28	.18	.09	.56	.46	.00	.29	1.20	0.00
	Rigid	.58	.00	.00	.55	.16	.49	.56	.10	.94	1.07	.00	.46	2.26	0.00
	GVW	18.1	1.9	3.8	31.2	14.2	27.7	42.7	16.0	45.7	62.6	8.5	45.6	82.0	0.0
N Lane1	Num	15	850	526	5	34	20	8	49	35	28	1	3	9	0
	Flex	.05	.00	.01	.67	.90	.84	.23	.43	1.51	2.39	1.03	1.77	2.08	0.00
	Rigid	.12	.01	.02	.89	1.02	1.42	.60	.53	2.82	5.74	1.34	3.99	3.88	0.00
	GVW	6.7	3.2	6.1	21.2	19.0	29.5	33.4	22.7	52.3	80.8	44.9	72.5	79.8	0.0
S Lane1	Num	3	833	638	3	40	33	4	50	37	19	1	2	6	0
	Flex	.27	.00	.00	.38	.16	.28	.18	.09	.56	.46	.00	.29	1.20	0.00
	Rigid	.58	.00	.00	.55	.16	.49	.56	.10	.94	1.07	.00	.46	2.26	0.00
	GVW	18.1	1.9	3.8	31.2	14.2	27.7	42.7	16.0	45.7	62.6	8.5	45.6	82.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: 2  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9