

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,067	769	3	26	11	2	35	80	36	0	2	23	0
	Flex	.60	.00	.00	.41	.37	.27	.94	.11	.65	.54	0.00	1.80	.90	0.00
	Rigid	1.29	.00	.00	.62	.37	.44	2.31	.12	1.16	1.28	0.00	3.78	1.62	0.00
	GVW	25.7	2.3	4.0	31.0	19.6	29.0	69.8	20.7	53.9	71.2	0.0	88.5	81.3	0.0
N	Num	2	528	388	2	13	5	1	18	35	18	0	2	11	0
	Flex	.26	.00	.00	.34	.28	.21	.66	.08	.47	.54	0.00	1.77	.74	0.00
	Rigid	.55	.00	.00	.54	.27	.34	1.71	.10	.82	1.21	0.00	3.74	1.26	0.00
	GVW	19.0	2.4	4.0	31.9	18.3	26.8	62.8	20.3	49.7	68.2	0.0	88.5	76.5	0.0
S	Num	2	539	381	1	13	6	2	17	45	18	0	1	13	0
	Flex	.75	.00	.00	.56	.46	.29	1.26	.14	.79	.53	0.00	.71	1.06	0.00
	Rigid	1.62	.00	.00	.75	.46	.49	2.96	.16	1.42	1.32	0.00	1.19	1.96	0.00
	GVW	27.8	2.3	4.0	30.2	20.8	30.1	78.8	21.2	57.1	73.2	0.0	60.1	87.2	0.0
N Lane1	Num	2	528	388	2	13	5	1	18	35	18	0	2	11	0
	Flex	.26	.00	.00	.34	.28	.21	.66	.08	.47	.54	0.00	1.77	.74	0.00
	Rigid	.55	.00	.00	.54	.27	.34	1.71	.10	.82	1.21	0.00	3.74	1.26	0.00
	GVW	19.0	2.4	4.0	31.9	18.3	26.8	62.8	20.3	49.7	68.2	0.0	88.5	76.5	0.0
S Lane1	Num	2	539	381	1	13	6	2	17	45	18	0	1	13	0
	Flex	.75	.00	.00	.56	.46	.29	1.26	.14	.79	.53	0.00	.71	1.06	0.00
	Rigid	1.62	.00	.00	.75	.46	.49	2.96	.16	1.42	1.32	0.00	1.19	1.96	0.00
	GVW	27.8	2.3	4.0	30.2	20.8	30.1	78.8	21.2	57.1	73.2	0.0	60.1	87.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Feb-2023

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9