

Idaho Transportation Department

Monthly WIM Distribution for Mar-2023

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,140	794	3	26	13	2	34	87	35	2	2	21	0
	Flex	.19	.00	.00	.60	.35	.37	.96	.12	.69	.57	.71	1.83	1.10	0.00
	Rigid	.40	.00	.00	.92	.34	.60	2.40	.14	1.19	1.35	.68	3.89	1.95	0.00
	GVW	14.5	2.4	4.2	35.0	18.9	30.2	74.8	20.9	54.3	70.4	44.1	82.0	84.3	0.0
N	Num	1	573	400	2	14	6	2	18	37	17	2	2	10	0
	Flex	.06	.00	.00	.63	.33	.47	.63	.12	.61	.71	.37	1.91	.97	0.00
	Rigid	.13	.00	.00	.92	.32	.75	1.29	.14	1.03	1.59	.35	4.11	1.67	0.00
	GVW	8.5	2.5	4.3	31.7	18.8	32.6	56.2	21.3	52.0	69.4	39.0	84.7	79.0	0.0
S	Num	2	566	394	2	13	7	2	17	49	19	1	1	11	0
	Flex	.28	.00	.00	.63	.36	.31	1.01	.12	.73	.45	2.41	.90	1.21	0.00
	Rigid	.60	.00	.00	.96	.36	.52	2.64	.14	1.27	1.15	2.38	1.57	2.22	0.00
	GVW	19.5	2.2	4.0	40.1	18.8	29.0	79.0	20.6	55.6	71.5	69.0	59.4	90.5	0.0
N Lane1	Num	1	573	400	2	14	6	2	18	37	17	2	2	10	0
	Flex	.06	.00	.00	.63	.33	.47	.63	.12	.61	.71	.37	1.91	.97	0.00
	Rigid	.13	.00	.00	.92	.32	.75	1.29	.14	1.03	1.59	.35	4.11	1.67	0.00
	GVW	8.5	2.5	4.3	31.7	18.8	32.6	56.2	21.3	52.0	69.4	39.0	84.7	79.0	0.0
S Lane1	Num	2	566	394	2	13	7	2	17	49	19	1	1	11	0
	Flex	.28	.00	.00	.63	.36	.31	1.01	.12	.73	.45	2.41	.90	1.21	0.00
	Rigid	.60	.00	.00	.96	.36	.52	2.64	.14	1.27	1.15	2.38	1.57	2.22	0.00
	GVW	19.5	2.2	4.0	40.1	18.8	29.0	79.0	20.6	55.6	71.5	69.0	59.4	90.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2023

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9