

# Idaho Transportation Department

## Monthly WIM Distribution for May-2023

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,641	987	3	48	18	4	59	77	36	1	2	16	0
	Flex	.50	.00	.00	.59	.33	.29	.69	.11	.80	.65	.00	.68	1.36	0.00
	Rigid	1.15	.00	.00	.78	.34	.48	1.79	.13	1.43	1.57	.00	1.31	2.58	0.00
	GVW	11.2	2.2	4.3	30.9	17.2	27.1	58.9	18.8	52.0	70.5	10.7	55.9	86.3	0.0
N	Num	2	971	420	2	21	6	2	29	27	15	1	2	5	0
	Flex	.00	.00	.00	.35	.17	.21	.23	.05	.42	.46	.00	.60	.89	0.00
	Rigid	.00	.00	.00	.44	.17	.31	.54	.05	.74	1.05	.00	1.20	1.47	0.00
	GVW	2.4	2.2	3.9	27.9	15.0	23.6	40.9	16.0	43.4	58.1	10.7	58.6	61.9	0.0
S	Num	1	669	608	2	29	14	3	33	53	22	0	2	11	0
	Flex	.85	.00	.00	.66	.39	.30	1.23	.14	.90	.67	0.00	.57	1.43	0.00
	Rigid	1.96	.00	.00	.83	.40	.52	3.24	.16	1.62	1.67	0.00	1.03	2.79	0.00
	GVW	17.0	2.4	4.4	28.9	17.8	28.5	75.0	19.9	53.9	73.5	0.0	49.3	90.4	0.0
N Lane1	Num	2	971	420	2	21	6	2	29	27	15	1	2	5	0
	Flex	.00	.00	.00	.35	.17	.21	.23	.05	.42	.46	.00	.60	.89	0.00
	Rigid	.00	.00	.00	.44	.17	.31	.54	.05	.74	1.05	.00	1.20	1.47	0.00
	GVW	2.4	2.2	3.9	27.9	15.0	23.6	40.9	16.0	43.4	58.1	10.7	58.6	61.9	0.0
S Lane1	Num	1	669	608	2	29	14	3	33	53	22	0	2	11	0
	Flex	.85	.00	.00	.66	.39	.30	1.23	.14	.90	.67	0.00	.57	1.43	0.00
	Rigid	1.96	.00	.00	.83	.40	.52	3.24	.16	1.62	1.67	0.00	1.03	2.79	0.00
	GVW	17.0	2.4	4.4	28.9	17.8	28.5	75.0	19.9	53.9	73.5	0.0	49.3	90.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2023

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9