

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,081	920	4	42	11	2	39	94	46	2	2	24	0
	Flex	.07	.00	.00	.63	.24	.29	.36	.16	.85	.67	.70	1.21	1.18	0.00
	Rigid	.14	.00	.00	.94	.24	.49	.71	.18	1.53	1.61	.65	1.60	2.32	0.00
	GVW	13.4	2.5	4.3	33.1	16.5	29.8	45.8	22.3	56.7	73.0	51.2	66.9	86.5	0.0
N	Num	1	546	464	2	23	5	1	21	43	20	2	1	12	0
	Flex	.22	.00	.00	.63	.19	.27	.45	.12	.65	.73	.97	.46	.96	0.00
	Rigid	.47	.00	.00	.95	.19	.44	.56	.14	1.12	1.66	.91	.54	1.65	0.00
	GVW	15.0	2.6	4.2	32.5	15.5	28.9	43.8	21.6	51.9	69.1	58.0	53.2	73.7	0.0
S	Num	2	535	456	2	19	6	2	18	51	27	2	2	12	0
	Flex	.02	.00	.00	.59	.31	.31	.26	.22	1.01	.60	.37	2.45	1.43	0.00
	Rigid	.04	.00	.00	.88	.31	.52	.82	.24	1.88	1.50	.34	3.40	3.07	0.00
	GVW	12.8	2.5	4.3	32.6	17.6	30.5	47.1	23.5	60.6	75.0	44.2	87.8	102.7	0.0
N Lane1	Num	1	546	464	2	23	5	1	21	43	20	2	1	12	0
	Flex	.22	.00	.00	.63	.19	.27	.45	.12	.65	.73	.97	.46	.96	0.00
	Rigid	.47	.00	.00	.95	.19	.44	.56	.14	1.12	1.66	.91	.54	1.65	0.00
	GVW	15.0	2.6	4.2	32.5	15.5	28.9	43.8	21.6	51.9	69.1	58.0	53.2	73.7	0.0
S Lane1	Num	2	535	456	2	19	6	2	18	51	27	2	2	12	0
	Flex	.02	.00	.00	.59	.31	.31	.26	.22	1.01	.60	.37	2.45	1.43	0.00
	Rigid	.04	.00	.00	.88	.31	.52	.82	.24	1.88	1.50	.34	3.40	3.07	0.00
	GVW	12.8	2.5	4.3	32.6	17.6	30.5	47.1	23.5	60.6	75.0	44.2	87.8	102.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2024

Site names: 00135
 County: Adams
 Funct Class: R Principal Arterial - Other
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4
 Daily Factor Grp: 5
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9