

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2024

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,467	1,682	5	94	31	7	82	132	53	1	3	27	0
	Flex	.05	.00	.00	.89	.35	.45	.67	.13	.94	.80	.01	.21	1.24	0.00
	Rigid	.10	.00	.00	1.28	.35	.76	1.25	.16	1.73	1.93	.01	.35	2.27	0.00
	GVW	7.7	2.7	4.8	34.8	17.4	31.8	51.1	21.0	56.1	75.9	14.8	44.3	83.6	0.0
N	Num	3	716	814	3	48	15	5	41	61	19	1	1	14	0
	Flex	.03	.00	.00	.99	.31	.39	.70	.14	.72	.84	.01	.21	1.23	0.00
	Rigid	.06	.00	.00	1.29	.31	.63	1.28	.17	1.25	2.01	.01	.31	2.24	0.00
	GVW	5.0	2.8	4.8	35.4	16.9	30.3	56.0	21.6	51.7	74.1	14.8	42.2	80.3	0.0
S	Num	2	751	868	3	46	16	6	42	71	34	0	2	14	0
	Flex	.08	.00	.00	.80	.38	.53	.76	.12	1.13	.75	0.00	.24	1.33	0.00
	Rigid	.16	.00	.00	1.41	.40	.96	1.61	.15	2.13	1.83	0.00	.38	2.54	0.00
	GVW	11.4	2.6	4.8	33.7	17.9	33.7	54.0	20.7	59.6	76.4	0.0	44.3	88.8	0.0
N Lane1	Num	3	716	814	3	48	15	5	41	61	19	1	1	14	0
	Flex	.03	.00	.00	.99	.31	.39	.70	.14	.72	.84	.01	.21	1.23	0.00
	Rigid	.06	.00	.00	1.29	.31	.63	1.28	.17	1.25	2.01	.01	.31	2.24	0.00
	GVW	5.0	2.8	4.8	35.4	16.9	30.3	56.0	21.6	51.7	74.1	14.8	42.2	80.3	0.0
S Lane1	Num	2	751	868	3	46	16	6	42	71	34	0	2	14	0
	Flex	.08	.00	.00	.80	.38	.53	.76	.12	1.13	.75	0.00	.24	1.33	0.00
	Rigid	.16	.00	.00	1.41	.40	.96	1.61	.15	2.13	1.83	0.00	.38	2.54	0.00
	GVW	11.4	2.6	4.8	33.7	17.9	33.7	54.0	20.7	59.6	76.4	0.0	44.3	88.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2024

Site names: 00135  
 County: Adams  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 4 Mi. N of Indian Valley Rd

Seasonal Factor Grp: 4  
 Daily Factor Grp: 5  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9