

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,343	2,073	1	49	49	3	32	200	27	2	2	25	0
	Flex	.00	.00	.00	.46	.41	.81	.66	.53	1.21	.76	.08	.61	.70	0.00
	Rigid	.00	.00	.00	.57	.42	1.46	1.30	.67	2.13	1.80	.09	.69	1.08	0.00
	GVW	1.3	3.4	4.1	23.0	18.2	32.4	32.2	26.2	57.2	69.4	23.2	35.6	56.2	0.0
N	Num	1	1,752	1,073	1	25	25	2	16	99	13	1	1	11	0
	Flex	.00	.00	.00	.80	.44	.95	.84	.67	1.29	.92	.12	1.22	.65	0.00
	Rigid	.00	.00	.00	1.04	.46	1.78	1.75	.91	2.24	2.26	.12	1.39	1.01	0.00
	GVW	1.5	3.3	4.0	34.1	18.3	33.6	36.4	28.1	56.7	72.2	24.7	44.1	54.2	0.0
S	Num	1	1,591	1,000	1	24	25	2	16	101	14	1	1	14	0
	Flex	.00	.00	.00	.42	.36	.66	.64	.40	1.15	.60	.04	.06	.74	0.00
	Rigid	.00	.00	.00	.54	.36	1.14	.77	.44	2.05	1.34	.05	.06	1.14	0.00
	GVW	1.1	3.5	4.3	21.2	18.1	31.2	27.5	24.2	57.8	68.5	20.8	26.3	57.3	0.0
N Lane1	Num	1	1,752	1,073	1	25	25	2	16	99	13	1	1	11	0
	Flex	.00	.00	.00	.80	.44	.95	.84	.67	1.29	.92	.12	1.22	.65	0.00
	Rigid	.00	.00	.00	1.04	.46	1.78	1.75	.91	2.24	2.26	.12	1.39	1.01	0.00
	GVW	1.5	3.3	4.0	34.1	18.3	33.6	36.4	28.1	56.7	72.2	24.7	44.1	54.2	0.0
S Lane1	Num	1	1,591	1,000	1	24	25	2	16	101	14	1	1	14	0
	Flex	.00	.00	.00	.42	.36	.66	.64	.40	1.15	.60	.04	.06	.74	0.00
	Rigid	.00	.00	.00	.54	.36	1.14	.77	.44	2.05	1.34	.05	.06	1.14	0.00
	GVW	1.1	3.5	4.3	21.2	18.1	31.2	27.5	24.2	57.8	68.5	20.8	26.3	57.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2017

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9