

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2017

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	3,270	2,008	1	57	90	3	38	242	49	3	2	25	0
	Flex	.00	.00	.00	.81	.47	.70	.53	.50	1.13	1.06	1.27	.99	.65	0.00
	Rigid	.00	.00	.00	.96	.49	1.25	.70	.67	1.97	2.51	1.48	1.16	1.07	0.00
	GVW	1.7	3.2	4.2	25.7	18.8	31.2	30.3	25.8	55.1	73.5	33.9	37.7	56.4	0.0
N	Num	1	1,695	1,027	1	28	46	2	19	122	18	1	1	11	0
	Flex	.00	.00	.00	.03	.60	.51	.83	.64	1.18	1.27	3.94	1.91	.72	0.00
	Rigid	.00	.00	.00	.03	.63	.82	1.17	.90	1.96	3.17	4.65	2.25	1.18	0.00
	GVW	1.6	3.2	4.0	13.6	19.6	27.1	32.1	26.3	51.8	67.1	41.5	45.8	58.4	0.0
S	Num	1	1,575	981	2	29	44	2	19	119	31	2	1	14	0
	Flex	.00	.00	.00	1.23	.32	.90	.42	.38	1.09	.90	.48	.10	.61	0.00
	Rigid	.00	.00	.00	1.45	.32	1.70	.55	.47	1.98	2.06	.57	.12	1.03	0.00
	GVW	1.6	3.3	4.3	33.8	17.9	35.5	30.6	25.3	58.5	76.8	34.2	33.4	54.9	0.0
N Lane1	Num	1	1,695	1,027	1	28	46	2	19	122	18	1	1	11	0
	Flex	.00	.00	.00	.03	.60	.51	.83	.64	1.18	1.27	3.94	1.91	.72	0.00
	Rigid	.00	.00	.00	.03	.63	.82	1.17	.90	1.96	3.17	4.65	2.25	1.18	0.00
	GVW	1.6	3.2	4.0	13.6	19.6	27.1	32.1	26.3	51.8	67.1	41.5	45.8	58.4	0.0
S Lane1	Num	1	1,575	981	2	29	44	2	19	119	31	2	1	14	0
	Flex	.00	.00	.00	1.23	.32	.90	.42	.38	1.09	.90	.48	.10	.61	0.00
	Rigid	.00	.00	.00	1.45	.32	1.70	.55	.47	1.98	2.06	.57	.12	1.03	0.00
	GVW	1.6	3.3	4.3	33.8	17.9	35.5	30.6	25.3	58.5	76.8	34.2	33.4	54.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2017

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9