

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2017

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	329	1,660	2	41	32	5	27	180	41	1	4	18	0
	Flex	.00	.00	.00	.12	.25	.33	.38	.28	.79	.46	.08	1.59	.49	0.00
	Rigid	.00	.00	.00	.11	.24	.54	.49	.36	1.38	1.06	.08	1.77	.82	0.00
	GVW	2.3	3.2	4.2	16.8	16.9	25.9	26.0	23.4	55.4	67.8	31.1	49.1	59.5	0.0
N	Num	0	188	875	1	20	19	2	13	89	18	0	2	8	0
	Flex	0.00	.00	.00	.04	.24	.37	.15	.31	.70	.53	0.00	.05	.23	0.00
	Rigid	0.00	.00	.00	.04	.24	.61	.26	.41	1.13	1.21	0.00	.05	.36	0.00
	GVW	0.0	3.2	4.0	14.2	16.1	27.2	27.4	26.7	51.0	66.6	0.0	26.4	49.1	0.0
S	Num	2	1,114	785	1	21	13	4	14	90	22	1	2	11	0
	Flex	.00	.00	.00	.19	.27	.26	.54	.23	.90	.40	.08	2.77	.67	0.00
	Rigid	.00	.00	.00	.18	.26	.42	.71	.28	1.68	.93	.08	3.10	1.13	0.00
	GVW	2.3	3.1	4.4	19.4	17.9	24.4	26.6	19.9	59.8	69.4	31.1	66.2	66.9	0.0
N Lane1	Num	0	188	875	1	20	19	2	13	89	18	0	2	8	0
	Flex	0.00	.00	.00	.04	.24	.37	.15	.31	.70	.53	0.00	.05	.23	0.00
	Rigid	0.00	.00	.00	.04	.24	.61	.26	.41	1.13	1.21	0.00	.05	.36	0.00
	GVW	0.0	3.2	4.0	14.2	16.1	27.2	27.4	26.7	51.0	66.6	0.0	26.4	49.1	0.0
S Lane1	Num	2	1,114	785	1	21	13	4	14	90	22	1	2	11	0
	Flex	.00	.00	.00	.19	.27	.26	.54	.23	.90	.40	.08	2.77	.67	0.00
	Rigid	.00	.00	.00	.18	.26	.42	.71	.28	1.68	.93	.08	3.10	1.13	0.00
	GVW	2.3	3.1	4.4	19.4	17.9	24.4	26.6	19.9	59.8	69.4	31.1	66.2	66.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Dec-2017

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9