

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	3,468	1,472	6	76	41	3	47	230	36	1	2	23	0
	Flex	.49	.02	.02	7.10	3.38	3.90	6.59	2.92	8.36	5.33	14.15	5.38	7.21	0.00
	Rigid	1.15	.02	.02	9.81	3.94	6.90	19.15	3.71	16.19	13.51	16.64	11.84	14.30	0.00
	GVW	24.2	4.6	7.5	45.4	29.7	50.1	119.0	44.5	93.7	115.9	92.9	92.7	118.5	0.0
N	Num	2	1,607	810	4	41	21	2	26	124	20	1	2	11	0
	Flex	.57	.00	.02	8.43	3.52	3.91	6.52	2.60	9.28	5.80	3.37	5.38	6.37	0.00
	Rigid	1.29	.01	.02	11.96	4.11	7.22	18.77	3.23	18.45	15.58	3.67	11.66	13.56	0.00
	GVW	22.6	4.4	7.8	51.2	30.0	52.0	119.6	43.3	98.9	124.5	62.3	92.2	112.2	0.0
S	Num	2	1,861	662	3	35	20	2	21	106	16	1	1	12	0
	Flex	.26	.03	.02	4.84	3.22	4.12	3.46	3.37	7.19	4.79	19.67	9.43	7.28	0.00
	Rigid	.72	.03	.02	6.04	3.74	6.99	10.67	4.37	13.31	11.05	23.47	20.23	13.63	0.00
	GVW	20.8	4.8	7.1	34.9	29.3	48.3	95.0	46.3	87.3	105.3	104.1	117.0	119.5	0.0
N Lane1	Num	2	1,607	810	4	41	21	2	26	124	20	1	2	11	0
	Flex	.57	.00	.02	8.43	3.52	3.91	6.52	2.60	9.28	5.80	3.37	5.38	6.37	0.00
	Rigid	1.29	.01	.02	11.96	4.11	7.22	18.77	3.23	18.45	15.58	3.67	11.66	13.56	0.00
	GVW	22.6	4.4	7.8	51.2	30.0	52.0	119.6	43.3	98.9	124.5	62.3	92.2	112.2	0.0
S Lane1	Num	2	1,861	662	3	35	20	2	21	106	16	1	1	12	0
	Flex	.26	.03	.02	4.84	3.22	4.12	3.46	3.37	7.19	4.79	19.67	9.43	7.28	0.00
	Rigid	.72	.03	.02	6.04	3.74	6.99	10.67	4.37	13.31	11.05	23.47	20.23	13.63	0.00
	GVW	20.8	4.8	7.1	34.9	29.3	48.3	95.0	46.3	87.3	105.3	104.1	117.0	119.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9