

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	3,542	1,668	6	88	44	4	62	289	45	1	2	9	0
	Flex	.14	.00	.00	.43	.27	.34	.63	.27	.98	.59	.80	.59	.73	0.00
	Rigid	.32	.00	.00	.50	.26	.57	1.61	.31	1.72	1.52	.76	1.23	1.23	0.00
	GVW	9.9	2.4	4.0	24.7	17.4	30.9	75.9	27.0	60.8	76.9	52.7	63.2	75.4	0.0
N	Num	2	1,649	901	4	46	22	4	34	149	24	1	2	5	0
	Flex	.19	.00	.00	.45	.22	.32	.50	.26	.92	.46	.43	.63	.78	0.00
	Rigid	.40	.00	.00	.54	.21	.55	1.29	.29	1.64	1.20	.40	1.31	1.31	0.00
	GVW	11.5	2.3	4.1	27.4	16.9	31.0	74.7	26.5	61.5	76.0	45.2	65.3	74.0	0.0
S	Num	2	1,893	767	2	42	22	2	28	140	22	1	1	5	0
	Flex	.05	.00	.00	.44	.34	.36	.89	.29	1.03	.70	1.09	.20	.65	0.00
	Rigid	.14	.00	.00	.52	.33	.60	2.20	.32	1.78	1.78	1.03	.42	1.13	0.00
	GVW	7.9	2.6	4.0	24.0	18.2	31.2	77.3	27.6	59.9	76.7	58.6	41.6	76.1	0.0
N Lane1	Num	2	1,649	901	4	46	22	4	34	149	24	1	2	5	0
	Flex	.19	.00	.00	.45	.22	.32	.50	.26	.92	.46	.43	.63	.78	0.00
	Rigid	.40	.00	.00	.54	.21	.55	1.29	.29	1.64	1.20	.40	1.31	1.31	0.00
	GVW	11.5	2.3	4.1	27.4	16.9	31.0	74.7	26.5	61.5	76.0	45.2	65.3	74.0	0.0
S Lane1	Num	2	1,893	767	2	42	22	2	28	140	22	1	1	5	0
	Flex	.05	.00	.00	.44	.34	.36	.89	.29	1.03	.70	1.09	.20	.65	0.00
	Rigid	.14	.00	.00	.52	.33	.60	2.20	.32	1.78	1.78	1.03	.42	1.13	0.00
	GVW	7.9	2.6	4.0	24.0	18.2	31.2	77.3	27.6	59.9	76.7	58.6	41.6	76.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00137
 County: Canyon
 Funct Class: R Principal Arterial - Other
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9