

# Idaho Transportation Department

## Monthly WIM Distribution for May-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	4,027	2,534	8	125	72	10	114	311	62	0	3	23	0
	Flex	.36	.00	.00	.89	.56	.93	.94	.45	1.76	1.18	0.00	2.09	2.23	0.00
	Rigid	.80	.00	.00	1.24	.59	1.81	2.30	.60	3.53	3.12	0.00	4.33	4.25	0.00
	GVW	12.5	3.6	5.6	35.6	19.7	38.4	66.7	27.2	66.3	83.8	0.0	78.1	91.4	0.0
N	Num	6	1,897	1,319	5	65	32	9	57	166	32	0	2	11	0
	Flex	.51	.00	.00	.43	.24	.48	.88	.14	1.07	.67	0.00	2.62	1.13	0.00
	Rigid	1.12	.00	.00	.57	.24	.92	2.21	.16	2.07	1.74	0.00	5.26	1.79	0.00
	GVW	14.5	2.6	4.5	30.5	16.7	34.6	69.3	21.4	59.9	78.6	0.0	87.0	69.2	0.0
S	Num	2	2,130	1,215	3	60	39	2	57	145	30	0	2	12	0
	Flex	.04	.00	.01	1.92	.93	1.33	1.17	.75	2.53	1.72	0.00	.56	3.02	0.00
	Rigid	.08	.00	.01	2.73	.99	2.59	2.75	1.03	5.16	4.55	0.00	1.16	5.97	0.00
	GVW	8.5	4.5	6.9	50.4	23.1	41.6	61.4	32.9	73.4	90.0	0.0	56.3	107.2	0.0
N Lane1	Num	6	1,897	1,319	5	65	32	9	57	166	32	0	2	11	0
	Flex	.51	.00	.00	.43	.24	.48	.88	.14	1.07	.67	0.00	2.62	1.13	0.00
	Rigid	1.12	.00	.00	.57	.24	.92	2.21	.16	2.07	1.74	0.00	5.26	1.79	0.00
	GVW	14.5	2.6	4.5	30.5	16.7	34.6	69.3	21.4	59.9	78.6	0.0	87.0	69.2	0.0
S Lane1	Num	2	2,130	1,215	3	60	39	2	57	145	30	0	2	12	0
	Flex	.04	.00	.01	1.92	.93	1.33	1.17	.75	2.53	1.72	0.00	.56	3.02	0.00
	Rigid	.08	.00	.01	2.73	.99	2.59	2.75	1.03	5.16	4.55	0.00	1.16	5.97	0.00
	GVW	8.5	4.5	6.9	50.4	23.1	41.6	61.4	32.9	73.4	90.0	0.0	56.3	107.2	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9