

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	3,924	2,377	8	115	72	10	92	319	53	1	3	19	0
	Flex	.42	.00	.01	1.50	.62	1.11	.91	.54	2.09	1.49	1.40	2.97	2.57	0.00
	Rigid	.93	.00	.01	2.15	.65	2.14	1.87	.71	4.19	3.85	1.37	5.41	4.74	0.00
	GVW	14.2	3.7	5.6	37.9	20.0	39.7	55.2	27.6	68.1	85.4	46.4	87.5	98.4	0.0
N	Num	6	1,845	1,250	5	58	33	8	48	166	28	1	3	9	0
	Flex	.36	.00	.01	.88	.35	.68	.87	.27	1.49	1.10	2.80	2.12	2.34	0.00
	Rigid	.80	.00	.01	1.25	.36	1.27	1.71	.34	2.95	2.90	2.74	4.48	3.67	0.00
	GVW	12.7	2.7	4.6	35.5	17.1	34.0	60.8	23.0	62.3	81.5	75.9	81.8	84.3	0.0
S	Num	2	2,079	1,126	4	57	39	2	45	153	25	1	1	10	0
	Flex	.75	.00	.01	1.81	.88	1.49	.81	.84	2.72	1.92	.01	6.20	2.75	0.00
	Rigid	1.66	.00	.01	2.61	.95	2.91	1.99	1.11	5.49	4.87	.01	9.57	5.63	0.00
	GVW	21.8	4.5	6.7	36.5	23.0	44.4	48.7	32.8	74.2	90.1	17.0	96.0	109.5	0.0
N Lane1	Num	6	1,845	1,250	5	58	33	8	48	166	28	1	3	9	0
	Flex	.36	.00	.01	.88	.35	.68	.87	.27	1.49	1.10	2.80	2.12	2.34	0.00
	Rigid	.80	.00	.01	1.25	.36	1.27	1.71	.34	2.95	2.90	2.74	4.48	3.67	0.00
	GVW	12.7	2.7	4.6	35.5	17.1	34.0	60.8	23.0	62.3	81.5	75.9	81.8	84.3	0.0
S Lane1	Num	2	2,079	1,126	4	57	39	2	45	153	25	1	1	10	0
	Flex	.75	.00	.01	1.81	.88	1.49	.81	.84	2.72	1.92	.01	6.20	2.75	0.00
	Rigid	1.66	.00	.01	2.61	.95	2.91	1.99	1.11	5.49	4.87	.01	9.57	5.63	0.00
	GVW	21.8	4.5	6.7	36.5	23.0	44.4	48.7	32.8	74.2	90.1	17.0	96.0	109.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2023

Site names: 00137  
 County: Canyon  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 1.4 Mi. S of Jct SH-19

Seasonal Factor Grp: 1  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 3

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9